

• Hardware

Comm. Controller	MU860 (16C550C compatible)
Bus	32-bit Universal PCI
Connector	DB62 female

• Serial Interface

Number of Ports	8
Serial Standards	CP-118U: RS-232/422/485 CP-138U: RS-422/485
Max. No. of Boards per PC	4

• Performance

Baudrate	50 bps to 921.6 kbps
----------	----------------------

• Serial Communication Parameters

Data Bits	5, 6, 7, 8
Stop Bits	1, 1.5, 2
Parity	None, Even, Odd, Space, Mark
Flow Control	RTS/CTS, XON/XOFF

• Serial Signals

RS-232	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
RS-422	TxD+(B), TxD-(A), RxD+(B), RxD-(A), GND
RS-485-4w	TxD+(B), TxD-(A), RxD+(B), RxD-(A), GND
RS-485-2w	Data+(B), Data-(A), GND

• Physical Characteristics

Dimensions	82 x 135 mm (3.22 x 5.31 in)
------------	------------------------------

• Driver Support

Windows	Windows 95/98/ME/NT/2000, Windows XP/2003/Vista/2008/7/8/8.1/10 (x86/x64), Windows 2008 R2/2012/2012 R2 (x64), DOS, Windows Embedded CE 5.0/6.0, Windows XP Embedded
Linux	Linux 2.4.x, 2.6.x, 3.x
Unix-like Systems	QNX 6, SCO OpenServer, UnixWare 7, Solaris 10, FreeBSD