

• Hardware

Comm. Controller	16C550C compatible
Bus	PCI Express x1
Connector	DB44 female

• Serial Interface

Number of Ports	4
Serial Standards	RS-232
Max. No. of Boards per PC	4

• Performance

Baudrate	50 bps to 921.6 kbps
----------	----------------------

• Serial Communication Parameters

Data Bits	5, 6, 7, 8
Stop Bits	1, 1.5, 2
Parity	None, Even, Odd, Space, Mark
Flow Control	RTS/CTS, XON/XOFF

• Serial Signals

RS-232	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
--------	--

• Physical Characteristics

Dimensions	67.21 x 103 mm (2.65 x 4.06 in)
------------	---------------------------------

• Driver Support

Windows	Windows 95/98/ME/NT/2000, Windows XP/2003/Vista/2008/7/8/8.1/10 (x86/x64), Windows 2008 R2/2012/2012 R2 (x64), DOS
Linux	Linux 2.4.x, 2.6.x, 3.x
Unix-like Systems	QNX 6, SCO OpenServer, UnixWare 7, Solaris 10
Note	Please refer to Moxa's website for the latest driver support information.

• Environmental Limits

Operating Temperature	0 to 55°C (32 to 131°F)
-----------------------	-------------------------