

• Hardware

Comm. Controller	MU860 (16C550C compatible)
Bus	32-bit Universal PCI
Connector	CP-104UL: DB44 female CP-104JU: RJ45 x 4

• Serial Interface

Number of Ports	4
Serial Standards	RS-232
Max. No. of Boards per PC	8

• Performance

Baudrate	50 bps to 921.6 kbps (supports non-standard baudrates)
----------	--

• Serial Communication Parameters

Data Bits	5, 6, 7, 8
Stop Bits	1, 1.5, 2
Parity	None, Even, Odd, Space, Mark
Flow Control	RTS/CTS, XON/XOFF, RTS Toggle (RS-232 only)

• Serial Signals

RS-232	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
--------	--

• Physical Characteristics

Dimensions	CP-104UL: 64.4 x 120 mm (2.53 x 4.72 in) CP-104JU: 83 x 120 mm (3.27 x 4.72 in)
------------	--

• Driver Support

Windows	Windows 95/98/ME/NT/2000, Windows XP/2003/Vista/2008/7/8/8.1/10 (x86/x64), Windows Server 2008 R2/2012/2012/2016 R2 (x64), DOS, Windows Embedded CE 5.0/6.0, Windows XP Embedded
Linux	Linux 2.4.x, 2.6.x, 3.x
Unix-like Systems	QNX 6, SCO OpenServer, UnixWare 7, Solaris 10, FreeBSD
Note	Please refer to Moxa's website for the latest driver support information.

• Environmental Limits

Operating Temperature	Standard Models: 0 to 55°C (32 to 131°F) Wide Temp. Models: -40 to 85°C (-40 to 185°F)
-----------------------	---