

## • Hardware

Comm. Controller	16C550C compatible
Bus	PCI Express x1
Connector	DB44 female

## • Serial Interface

Number of Ports	4
Serial Standards	RS-232/422/485
Max. No. of Boards per PC	4

## • Serial Line Protection

Electrical Isolation	2 kV (CP-114EL-I only)
----------------------	------------------------

## • Performance

Baudrate	50 bps to 921.6 kbps
----------	----------------------

## • Serial Communication Parameters

Data Bits	5, 6, 7, 8
Stop Bits	1, 1.5, 2
Parity	None, Even, Odd, Space, Mark
Flow Control	RTS/CTS, XON/XOFF

## • Serial Signals

RS-232	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
RS-422	TxD+(B), TxD-(A), RxD+(B), RxD-(A), GND
RS-485-4w	TxD+(B), TxD-(A), RxD+(B), RxD-(A), GND
RS-485-2w	Data+(B), Data-(A), GND

## • Physical Characteristics

Dimensions	CP-114EL: 67.21 x 103 mm (2.65 x 4.06 in) CP-114EL-I: 67.21 x 135 mm (2.65 x 5.31 in)
------------	--

## • Driver Support

Windows	Windows 95/98/ME/NT/2000, Windows XP/2003/Vista/2008/7/8/8.1/10 (x86/x64), Windows 2008 R2/2012/2012 R2 (x64), DOS
---------	--