

• USB Interface

Compliance	USB 1.0/1.1 compliant, USB 2.0 compatible
Connector	USB Type A
Speed	12 Mbps (Full-Speed USB)

• Serial Interface

Number of Ports	1
Serial Standards	RS-422/485
Connector	DB9 male
Electrical Isolation	2 kV (UPort 1130I and 1150I)

• Performance

Baudrate	50 bps to 921.6 kbps
----------	----------------------

• Serial Communication Parameters

Data Bits	5, 6, 7, 8
Stop Bits	1, 1.5, 2
Parity	None, Even, Odd, Space, Mark
Flow Control	RTS/CTS, XON/XOFF
FIFO	64 bytes

• Serial Signals

RS-232	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
RS-422	TxD+(B), TxD-(A), RxD+(B), RxD-(A), GND
RS-485-4w	TxD+(B), TxD-(A), RxD+(B), RxD-(A), GND
RS-485-2w	Data+(B), Data-(A), GND
RS-485 Data Direction	ADDO® (Automatic Data Direction Control)

• Operating Systems

Windows Real COM Drivers	Windows 95/98/ME/NT/2000, Windows XP/2003/Vista/2008/7/8/8.1/10 (x86/x64), Windows 2012 (x64), Windows Embedded CE 5.0/6.0
Linux Real TTY Drivers	Linux 2.4.x, 2.6.x, 3.x Note: Please refer to Moxa's website for the latest driver support information.