

# Covered Links

Installation accessories for metering enclosures



- Suitable for domestic and commercial metering applications.

Conformity / Approvals:

- UL94, V0 rating, 960°C glow wire test
- Tunnel type terminals AS3000:2007: Clause 2.9.4
- Numbering to AS3000 regulations
- Designed to Australian regulations
- 400A product test report (completed by B&R)
- Complies to AS5112



## ORDERING GUIDE

Part Number			Description	No. of Tunnels	Maximum tunnel	Screws	Amps	Range
Clear	Red	Black						
LK5C35	LK5R35	LK5B35	Link 5 Terminals Max 35mm	5	35mm	Steel	100	Small
LK5C	LK5R	LK5B	Link 5 Terminals	5	16mm	Steel	100	Small
LK6C35	LK6R35	LK6B35	Link 6 Terminals Max 35mm	6	35mm	Steel	100	Small
LK7C35	LK7R35	LK7B35	Link 7 Terminals Max 35mm	7	35mm	Steel	100	Small
LK7C	LK7R	LK7B	Link 7 Terminals	7	16mm	Steel	100	Small
LK10C35	LK10R35	LK10B35	Link 10 Terminals Max 35mm	10	35mm	Steel	100	Medium
LK10C	LK10R	LK10B	Link 10 Terminals	10	16mm	Steel	100	Medium
LK13C35	LK13R35	LK13B35	Link 13 Terminals Max 35mm	13	35mm	Steel	100	Medium
LK18C	LK18R	LK18B	Link 18 Terminals	18	16mm	Steel	100	Medium
LKT4C35	LKT4R35	LKT4B35	Link T Shaped 4 Terminals Max 35mm	4	35mm	Brass	140	T-Shape
LK165A7C70	LK165A7R70	LK165A7B70	Link 165A 7 Terminals Max 70mm	7	70mm	Brass	165	165amp
LK165A13C70	LK165A13R70	LK165A13B70	Link 165A 13 Terminals Max 70mm	13	70mm	Brass	165	165amp
-	-	LK250A4B35	Link 100A 4 Terminals Max 35mm	4	35mm	Steel	100	Vic Link
LK400A7C150	LK400A7R150	LK400A7B150	Link 400A 7 Terminals Max 150mm	7	150mm	Brass	400	400amp
LK400A13C150	LK400A13R150	LK400A13B150	Link 400A 13 Terminals Max 150mm	13	150mm	Brass	400	400amp