

Lighting: Tank Light, EHTK Series



Flameproof Zone 1 & 2 – 22

Specification

Body material : Marine grade copper-free aluminium alloy with polyester powder coated, RAL 7032 (grey)
Lens : Heat and impact resistant glass

Technical Data

Hazardous Area	Gas	Dust
Zones	1 & 2	22
Conforming to ATEX	Ex II 2G	Ex II 2D
Symbol of Protection ATEX	Ex db IIB Gb	Ex tc IIIC Dc
Symbol of Protection IEC		
Standard	ATEX Directive 2014/34/EU, std. EN 60079-0:2012 + A11:2013, EN 60079-1:2014, EN 60079-31:2014	
	IECEX Scheme, std. IEC 60079-0:2011, IEC 60079-1:2014, IEC 60079-31:2013	
Ambient Temperature	-20 °C to +55 °C	
Index of Protection	IP54	
Mounting	Pendant mount	
Rated Voltage	220V.AC. ±5% 50Hz.	

Catalogue Number and Dimension

EHTK - XX □

Series: Lamp Watt: Option:
 (see catalogue S = On/Off Switch
 number table) (3A/ 220V.)

Lamp Watt	Cat. No.	Voltage	Lamp Model	Temp. Class (for zone 1 & 2)		Max. Surface Temp (for zone 22)		Volume (dm³)	Approx. Weight (kgs.)
				Ta 40 °C	Ta 55 °C	Ta 40 °C	Ta 55 °C		
Halogen									
75W.	EHTK-75 □	220V. 50Hz.	PAR 30 Halogen	T2	T2	T200°C	T200°C	3.40	5.15
LED									
9W.	EHTK-09 □	220V. 50Hz.	PAR 30 9W	T6	T6	T80°C	T80°C	3.40	5.15



Tank Light



Tank Light with Switch

