

Powerpack PLUS PRO Series

ONLINE UPS
1-3kVA
Single Phase / Single Phase

Small Network, Servers and other
IT Equipments



- 1 SNMP
- 1 Drycontact Card
- 2 USB



- Online-Double Conversion (PFC)
- Full Digital Control (DSP)
- Output Power Factor: 0.8 (0.9 Optional)
- Economic Operation Mode (ECO)
- Wide Input-Voltage Range
- Self-Testing When UPS Startup
- Cold Start (DC)
- Multifunctional Protection
- Output Bypass Settable
- Input Neutral and Live Wires Reverse Detection
- Optimized Battery Configuration: (1k:24VDC, 2k:48VDC, 3k:72VDC)
- Charger Extendible
- USB Port (Optional), USB is of Automatic Priority When USB & RS232 Work Together
- Intelligent Slot (Optional): USB /SNMP /Dry Contact Board



- 1 LCD
- 2 Scroll Button
- 3 Up / Down
- 4 Alarms
- 5 Bypass Led
- 6 Battery Led
- 7 Normal

1kVA • 2kVA • 3kVA

MODEL							
Capacity		1kVA / 800W		2kVA / 1600W		3kVA / 2400W	
INPUT							
Rated Voltage		220/230/240 VAC					
Voltage Range		115VAC~295VAC					
Frequency Range		50/60Hz ±10% (Auto Sensing)					
Power Factor		≥0.98					
Bypass Voltage		186VAC~252VAC					
Current Harmonic		<3% (Linear Load)					
OUTPUT							
Rated Voltage		200/208/220/230/240VAC±1% (Optional)					
Power Factor		0.8 (0.9 Optional)					
Output Frequency	Utility Mode	Follow Utility					
	Battery Mode	(50/60±0.2%) Hz					
Crest Factor		3:1					
Transfer Time		(Utility ← → Battery)=0ms					
		(Utility ← → Battery)<4ms					
Overload Capacity	Battery Mode	108% ±5% <Load ≤150% ±5% Exceed 30s, Cut off and Alarm, 150% ±5% <Load <200% ±5% Exceed 300ms, Cut off and Alarm					
	Utility Mode	108% ±5% < Load ≤150% ±5% Exceed 30s, Transfer to Bypass and Alarm, 150% ±5% < Load <200% ±5% Exceed 300ms, Transfer to Bypass and Alarm					
Efficiency	Utility Mode	86%					
	Battery Mode	84%					
THD		≤3% (100% linear load)					
		≤5% (100% non-linear load)					
BATTERY							
Voltage		24VDC	24VDC	48VDC	48VDC	72VDC	72VDC
Battery Configuration		2x12V/7AH	-	4x12V/7AH	-	6x12V/7AH	-
Type		12V/7AH (Standard)					
Backup Time		50% Load ≥5min (Standard), Long Time Unit Depends on the Capacity of External Batteries					
Charge Current (A)		1A	4A	1A	4A	1A	4A
OPERATING ENVIRONMENT							
Temperature		0~40°C					
Humidity		0%~95% (Non-Condensing)					
Noise Level		<45dB					
Storage Temperature		-25~55°C					
Altitude		<1500m					
OTHER							
Communication Interface		RS232 Optional (USB Port, USB Card, SNMP Card, Dry Contact Card)					
Unit Dimensions W x D x H (mm)		144 x 361 x 215			191 x 428 x 337		
Weight (kg)		10.2/11	5.2/6	19.5/21.1	9.5/11.1	24/25.6	9.7/11.3
STANDARDS							
Safety		IEC/EN62040-1;IEC/EN60950-1					
EMC		IEC/EN62040-2;IEC61000-4-2;IEC61000-4-3;IEC61000-4-4; IEC61000-4-5;IEC61000-4-6;IEC61000-4-8					

Makelsan reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Makelsan products previously or subsequently sold. Makelsan does not guarantee the items of the accuracy and completeness.