## LINE INTERACTIVE UPS 650-2000VA



Personal Computers, Workstation, Printer







- Output
- Input
- Fuse
- Output Bypass
- RCJ11/RJ45
- 6 RS232/USB





- LED Display or LCD Display for Option
- Microprocessor-Based Digital Control
- Boost and Buck AVR for Voltage Stabilization
- Frequency Adaptive
- Humanized Alarm System
- Automatically Diagnose When Starts
- O Cold Start
- Auto Restart While AC is Recovering
- Simulated Sine Wave Output
- Intelligent Battery Management
- Short Circuit and Over Discharged Protection
- Automatically Charging Battery at UPS Off Mode
- Shut Down When No Load Connected at Battery Mode
- Optional RS232/USB Communication Port and RCJ11/RJ45 Protection







MODEL						
Capacity		650VA/360W	850VA/480W	1000VA/720W	1500VA/900W	2000VA/1200W
INPUT						
Voltage		100V /110 V/120VAC ±25% or 220V/230V/240VAC ±25% (-35% Optional)				
Frequency		50/60 Hz ±10% (Auto Sensing)				
OUTPUT						
Voltage		100V /110 V/120VAC ±10% or 220V/230V/240VAC ±10%				
Frequency		50/60 Hz ±1% (Auto Sensing)				
Waveform		AC Mode: Pure sine wave, Battery mode; Simulated sine wave				
Crest Factor		3:1				
Transfer Time		Typical 2-7ms, 10ms max				
BATTERY						
DC Voltage		12V 24V				
Configuration		1x12V/7.0Ah	1x12V/9.0Ah	2x12V/7.0Ah 2x12V/9.0Ah		
Typical Recharge Time		6-8 Hours Recover to 90% Capacity				
PROTECT	ION					
Full Protection		Short Circuit, Battery over-charge and over discharge protection				
PHYSICAL	Ĺ					
	Dimension (mm) WxDxH	95x320x165		125x320x220		125x380x220
Metal Case	Packing Dimension (mm) WxDxH	145x375x230		180x390x295		180x450x295
	Net Weight (kg)	5.5	6.7	10.5	12.6	14.0
	Gross Weight (kg)	6.0	7.2	11.2	13.4	14.8
	Quantity in box	3 pcs		2 pcs		
ENVIRON	MENT					
Temperatu	ure			0~40°C		
Humidity		20~90% RH @ 0~40 °C (non-condensing)				
Noise Level				≤ 45dB (1m)		
MANAGE	MENT					
USB / RS -232 /SNMP (Optional)		Supports Windows 98/2000/2003/XP/Vista/2008/Windows 7/8				

Makelsan reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Makelsan products previously or subsequently sold. Makelsan does not guarantee the items of the accuracy and completeness.