SIRCOVER

Manual transfer switches
from 125 to 3200 A

svr_151_a

SIRCOVER
250 A

svr_125_a_1_cat

Bypass ATS
500 A

The solution for

- Manufacturing industry
- Power distribution

Strong points

- A complete range
- Easy connections
- Stable positions

Conformity to standards

- IEC 60947-6-1
- IEC 60947-3
- GB 14048-11

Approvals and certifications[1]

[1] *Product reference on request.*

Function

SIRCOVER AC are manual multipolar transfer switches with positive break indication.
The family includes three ranges:

- **SIRCOVER AC** for open transition switching (I-0-II),
- **SIRCOVER** for overlapping contact switching (I-I+II-II), and
- **SIRCOVER Bypass**. This version is a combination of three interlocked switches enabling use with 3 + 6 poles or 4 + 8 poles.

They provide switching, source inversion and transfer under load for two low voltage power circuits, as well as their safety isolation by double breaking per pole.

Advantages

A complete product range
Three versions of the SIRCOVER are available to ensure compatibility with the maximum number of applications: SIRCOVER AC (I-0-II) with improved on load switching characteristics and isolation position, SIRCOVER with overlapping contacts (I-I+II-II) and a BYPASS version.

Easy connections
A copper bar connection kit is available for 2000 to 3200 A ratings. It enables various types of connection: flat or edgewise connection with top or bottom bridging.

Stable positions
SIRCOVERs have three stable positions which are not affected by voltage drops or vibrations, thus protecting your load against network interference.

Improved on load switching
Thanks to its AC-23 and AC-33 characteristics, which are tested in accordance with standards IEC 60947-3 and IEC 60947-6-1, the SIRCOVER AC enables secure and reliable switching on all types of load, without the need for pre-breaking upstream.

socomec Innovative Power Solutions

What you need to know

- SIRCOVER (I-0-II) switches have **3 stable positions**, and are available as 3 or 4 pole devices from 125 to 3200 A. They are available enclosed in a steel or polyester enclosure from 125 to 1600 A.
- SIRCOVER switches with **overlapping contacts** (I-I+II-II) are available as 3 or 4 pole devices from 125 to 1600 A.
- With 3 stable positions (I-0-II), SIRCOVER Bypass are a combination of three interlocked switches enabling the use with 3+6 poles or 4+8 poles from 125 to 1600 A.
- All SIRCOVER can be utilised with a **direct front** or **external operation** handle.

svr_136_a_1_x_cat

- **Copper bar connection kits** enable the connection between the two power terminals of the same pole (fig.1 & fig.2) and the bridging of the poles on the top or bottom side of the switch (fig.3), for ratings 2000, 2500 and 3200 A.

Fig. 1

acces_226_c_2_cat

Top or bottom **flat connection**

Fig. 2

acces_229_b_2_cat

Edgewise connection
Top or bottom

Fig. 3

acces_231_a_1_cat

Top or bottom **bridging connection**

References

SIRCOVER AC I-0-II

Rating (A) / Frame size	No. of poles	Switch body	Direct handle	External handle	Shaft for external handle	Bridging bars	Auxiliary contact	Terminal shrouds	Terminal screens
125 A / B3	3 P	41AC **3013**	J2 type Blue 1122 **1111** Red 1123 **1111**	S2 type Black IP55 1421 **2113** Black IP65 1423 **2113**(1)	200 mm 1400 **1020** 320 mm 1400 **1032**(1)	3 P 4109 **3019** 4 P 4109 **4019**	1st/2nd contact NO/NC 4109 **0021**(2)	3 P 2694 **3014**(3)(4) 4 P 2694 **4014**(3)(4)	3 P 1509 **3012** 4 P 1509 **4012**
	4 P	41AC **4013**							
160 A / B3	3 P	41AC **3016**							
	4 P	41AC **4016**							
200 A / B3	3 P	41AC **3020**							
	4 P	41AC **4020**							
250 A / B4	3 P	41AC **3025**				4109 **3025**		3 P 2694 **3021**(3)(4) 4 P 2694 **4021**(3)(4)	3 P 1509 **3025** 4 P 1509 **4025**
	4 P	41AC **4025**				4109 **4025**			
315 A / B4	3 P	41AC **3031**				3 P 4109 **3039** 4 P 4109 **4039**			
	4 P	41AC **4031**							
400 A / B4	3 P	41AC **3040**							
	4 P	41AC **4040**							
500 A / B5	3 P	41AC **3050**				4109 **3050**		3 P 2694 **3051**(3)(4) 4 P 2694 **4051**(3)(4)	3 P 1509 **3063**(5) 4 P 1509 **4063**(5)
	4 P	41AC **4050**				4109 **4050**			
630 A / B5	3 P	41AC **3063**				4109 **3063**			
	4 P	41AC **4063**				4109 **4063**			
800 A / B6	3 P	41AC **3080**	C1 type Black 2799**7052**	S4 type Black IP65 1443 **3113**	200 mm 1401 **1520** 320 mm 1401 **1532**(1)	3 P 4109 **3080** 4 P 4109 **4080**			3 P 1509 **3080**(5) 4 P 1509 **4080**(5)
	4 P	41AC **4080**							
1000 A / B6	3 P	41AC **3100**							
	4 P	41AC **4100**							
1250 A / B6	3 P	41AC **3120**				4109 **3120**			
	4 P	41AC **4120**				4109 **4120**			
1600 A / B7	3 P	41AC **3160**				3 P 4109 **3160** 4 P 4109 **4160**			3 P 1509 **3160**(5) 4 P 1509 **4160**(5)
	4 P	41AC **4160**							
2000 A / B8	3 P	41AC **3200**	S5 type Black 2799 **7042**	S5 type Black IP65 1453 **8113**	200 mm 2799 **3015** 320 mm 2799 **3018**(1) 450 mm 2799 **3019**	(6)	1st/2nd contact NO/NC included		included
	4 P	41AC **4200**							
2500 A / B8	3 P	41AC **3250**							
	4 P	41AC **4250**							
3200 A / B8	3 P	41AC **3320**							
	4 P	41AC **4320**							

(1) Standard.
(2) 2 pieces: one for position I and one for position II.
(3) To fully shroud front, rear, top and bottom 4 references required.
(4) To shroud front switch top and bottom 2 references required.
(5) 2 pieces: one for top side and another for bottom side.
(6) See "Copper bar connection kits" page 20.

socomec
Innovative Power Solutions

Also available

SIRCOVER AC I-I+II-II

From 125 to 1600 A, these manual transfer switches are used for switching from one normal source to a backup in open transition conditions. However both sources must be synchronous.

Reference: 46AC XYYY

X = number of poles	Y = rating (A)	
3 : 3 poles	013 : 125	050 : 500
4 : 4 poles	016 : 160	063 : 630
	020 : 200	080 : 800
	025 : 250	100 : 1000
	031 : 315	120 : 1250
	040 : 400	160 : 1600

SIRCOVER AC BY-PASS

From 125 up to 1600 A, these manual transfer switches enable the isolation and the bypassing of the backup source, using an uninterruptible power supply for instance, thanks to 3 compact interlocked switches in a single product.

Two bypass versions are available, one with open transition and the second one with overlapping contacts.

commut_034_R_1_X_cat

Reference: 4ZAC XYYY

Z = switching type	X = number of poles	Y = rating (A)	
1 : I - 0 - II	7 : 3 + 6 poles	013 : 125	050 : 500
6 : I - I+II - II	9 : 4 + 8 poles	016 : 160	063 : 630
		020 : 200	080 : 800
		025 : 250	100 : 1000
		031 : 315	120 : 1250
		040 : 400	160 : 1600

Accessories

Direct operation handle

SIRCOVER AC I-0-II and I-I+II-II				
Rating (A)	**Frame size**	**Handle colour**	**Handle type**	**Reference**
125 … 630	B3 … B5	Blue	J2 type	1122 **1111**
125 … 630	B3 … B5	Red	J2 type	1123 **1111**
800 … 1600	B6 … B7	Black	C1 type	2799 **7052**
2000 … 3200	B8	Black	S5 type	2799 **7042**[1]

SIRCOVER AC BYPASS				
Rating (A)	**Frame size**	**Handle colour**	**Handle type**	**Reference**
125 … 200	B3	Blue	J2 type	1122 **1111**
250 … 630	B4 … B5	Black	C1 type	2799 **7052**
800 … 1600	B6 … B7	Black	C2 type	2799 **7012**[1]

J2 type handle

C1 type handle

C2 type handle

(1) Double lever handle

External operation handle

Use

Door interlocked external front operation handles include an escutcheon, are padlockable and must be utilised with an extension shaft.

SIRCOVER AC I-0-II and I-I+II-II					
Rating (A)	**Frame size**	**Switching type**	**External IP**[1]	**Handle**	**Reference**
125 … 630	B3 … B5	I - 0 - II	IP55	S2 type	1421 **2113**
125 … 630	B3 … B5	I - 0 - II	IP65	S2 type	1423 **2113**
125 … 630	B3 … B5	I - I+II - II	IP65	S2 type	1423 **2114**
800 … 1600	B6 … B7	I - 0 - II	IP65	S4 type	1443 **3113**[2]
800 … 1600	B6 … B7	I - I+II - II	IP65	S4 type	1443 **3114**[2]
2000 … 3200	B8	I - 0 - II	IP65	S5 type	1453 **8113**[2]

(1) IP: protection degree according to IEC 60529 standard.
(2) Double lever handle.

SIRCOVER AC BYPASS					
Rating (A)	**Frame size**	**Switching type**	**External IP**[1]	**Handle**	**Reference**
125 … 200	B3	I - 0 - II	IP55	S2 type	1421 **2113**
125 … 200	B3	I - 0 - II	IP65	S2 type	1423 **2113**
250 … 630	B4 … B5	I - 0 - II	IP65	S3 type	1433 **3113**
800 … 1600	B6 … B7	I - 0 - II	IP65	V2 type	4199 **7146**

(1) IP: protection degree according to IEC 60529 standard.

S2 type handle

S3 type handle

S4 type handle

S5 type handle

Alternative S type handle cover colours

Use

For single lever handles S1, S2, S3 type and for double lever handle S4 type.
Other colours: please consult us.

Colour	To be ordered in multiples of	Handle	Reference
Light grey	50	S2, S3 type	1401 **0001**
Dark grey	50	S2, S3 type	1401 **0011**
Light grey	50	S4 type	1401 **0031**
Dark grey	50	S4 type	1401 **0041**

S type handle adapter

Use

Enables S type handles to be fitted in place of existing older style SOCOMEC handles. Adapter can also be utilised as a spacer to increase the distance between the panel door and the handle lever.

Dimensions

Adds 12 mm to the depth.

Colour	To be ordered in multiples of	External IP[1]	Reference
Black	1	IP65	1493 **0000**

(1) IP: protection degree according to IEC 60529 standard.

Shaft guide for external operation

Use

To guide the shaft extension into the external handle.

This accessory enables the handle to engage the extension shaft with a misalignment of up to 15 mm.

Required for shaft lengths over 320 mm.

Description	Reference
Shaft guide	1429 **0000**

acces_260_a_2_cat

Shaft for external handle

Use

Standard lengths:
- 200 mm,
- 320 mm,
- 450 mm.

Other lengths: please consult us.

acces_369_a_1_cat

acces_144_b_1_cat

SIRCOVER AC I-0-II and I-I+II-II				
Rating (A)	**Frame size**	**Length (mm)**	**Dimension X (mm)**	**Reference**
125 … 400	B3 … B4	200	210 … 310	1400 **1020**
125 … 400	B3 … B4	320	210 … 430	1400 **1032**
500 … 630	B5	200	280 … 390	1400 **1020**
500 … 630	B5	320	280 … 510	1400 **1032**
800 … 1600	B6 … B7	200	425 … 577	1401 **1520**
800 … 1600	B6 … B7	320	425 … 697	1401 **1532**
2000 … 3200	B8	200	653 … 803	2799 **3015**
2000 … 3200	B8	320	653 … 923	2799 **3018**
2000 … 3200	B8	450	653 … 1053	2799 **3019**

SIRCOVER AC BYPASS				
Rating (A)	**Frame size**	**Length (mm)**	**Dimension X (mm)**	**Reference**
125 … 200	B3	200	320 … 450	1400 **1020**
125 … 200	B3	320	320 … 570	1400 **1032**
250 … 400	B4	200	298 … 420	1401 **1520**
250 … 400	B4	320	298 … 540	1401 **1532**
500 … 630	B5	200	417 … 539	1401 **1520**
500 … 630	B5	320	417 … 659	1401 **1532**
800 … 1600	B6 … B7	200	550 … 680	2799 **3015**
800 … 1600	B6 … B7	320	550 … 800	2799 **3018**
800 … 1600	B6 … B7	450	550 … 930	2799 **3019**

acces_202_a_1_x_cat

Bridging bars

Use

For creating a common connection between switches I & II, on the top or bottom side of the SIRCOVER, to enable, for example, the load to be fed from either incoming source (I or II).

For SIRCOVER Bypass, two sets of bridging bars are required (3/6 pole or 4/8 pole switch).

Rating (A)	Frame size	No. of poles	Section (mm)	Reference
125 … 200	B3	3 P	20 x 2.5	4109 **3019**
125 … 200	B3	4 P	20 x 2.5	4109 **4019**
250	B4	3 P	25 x 2.5	4109 **3025**
250	B4	4 P	25 x 2.5	4109 **4025**
315 … 400	B4	3 P	32 x 5	4109 **3039**
315 … 400	B4	4 P	32 x 5	4109 **4039**
500	B5	3 P	32 x 5	4109 **3050**
500	B5	4 P	32 x 5	4109 **4050**
630	B5	3 P	50 x 5	4109 **3063**
630	B5	4 P	50 x 5	4109 **4063**
800 … 1000	B6	3 P	50 x 6	4109 **3080**
800 … 1000	B6	4 P	50 x 6	4109 **4080**
1250	B6	3 P	60 x 8	4109 **3120**
1250	B6	4 P	60 x 8	4109 **4120**
1600	B7	3 P	90 x 10	4109 **3160**
1600	B7	4 P	90 x 10	4109 **4160**

SIRCOVER AC I-0-II and SIRCOVER I-I+II-II

acces_205_a_2_cat

acces_041_a_1_cat

svr_124_a_1_cat

SIRCOVER BYPASS

acces_208_a_2_cat

svr_068_a_1_x_cat

Accessories (continued)

Copper bar connection kits from 2000 to 3200 A - SIRCOVER

Use

Enables:
- connection between the two power terminals of the same pole for 2000 to 3200 A ratings (Fig. 1 and Fig 2)
- top or bottom bridging connection (Fig. 3).

For 3200 A rating, the connection pieces (part A) are delivered bridged from factory. Bolt sets must be ordered separately.

Further details for these specific accessories are available in the user guide downloadable from www.socomec.com.

Fig. 1

acces_226_b_1_x_cat

acces_232_a_1_cat

Top or bottom flat connection - Fig. 1

Rating (A)	Frame size	Piece	Quantity to order per pole(1)	Reference
2000 … 2500	B8	Connection - part A	2	2619 **1200**
2000 … 2500	B8	Bolt set - part B	2	2699 **1200**
3200	B8	Connection - part A		included
3200	B8	Bolt set - part B	2	2699 **1200**

(1) Example for 3 pole device equipped upstream only: Order 3 times the indicated quantities.

Fig. 2

acces_228_b_1_x_cat

acces_233_a_1_cat

Top or bottom edgewise connection - Fig. 2

Rating (A)	Frame size	Piece	Quantity to order per pole(1)	Reference
2000 … 2500	B8	Connection - part A	2	2619 **1200**
2000 … 2500	B8	T piece - part C	2	2629 **1200**(2)
2000 … 2500	B8	Bracket- part D	2	2639 **1200**(2)
3200	B8	Connection - part A		included
3200	B8	T piece - part C	2	2629 **1200**(2)
3200	B8	Bracket- part D	2	2639 **1200**(2)

(1) Example for 3 pole device equipped upstream only: Order 3 times the indicated quantities.
(2) Bolt set is provided with the accessories.

Fig. 3

acces_230_b_1_x_cat

acces_234_a_1_cat

Top or bottom bridging connection - Fig. 3

Rating (A)	Frame size	Piece	Quantity to order per pole(1)	Reference
2000 … 2500	B8	Connection - part A	2	2619 **1200**
2000 … 2500	B8	Bolt set - part B	2	2699 **1200**
2000 … 2500	B8	Bar - part E	1	4109 **0320**(2)
2000 … 2500	B8	T piece - part C	1	2629 **1200**(2)
3200	B8	Connection - part A		included
3200	B8	Bolt set - part B	2	2699 **1200**
3200	B8	Bar - part E	1	4109 **0320**(2)
3200	B8	T piece - part C	1	2629 **1200**(2)

(1) Example for 3 pole device equipped upstream only: Order 3 times the indicated quantities.
(2) Bolt set is provided with the accessories.

Auxiliary contact

Use

Pre breaking and signalling of positions I and II: 1 or 2 NO/NC auxiliary contacts in each position.

Low level auxiliary contacts: please consult us.

Connection to the control circuit

By 6.35 mm fast-on terminal.

Electrical characteristics

30 000 operations.

svr_058_a_1_cat

acces_065_a_1_cat

Characteristics

Rating (A)	Frame size	Nominal current (A)	Operating current I_e (A) 250 VAC AC-13	400 VAC AC-13	24 VDC DC-13	48 VDC DC-13
125 … 3200	B3 … B8	16	12	8	14	6

NO/NC changeover contact			
Rating (A)	**Frame size**	**Contact(s)**	**Reference**
125 … 1600	B3 … B7	1st/2nd	4109 **0021**
2000 … 3200	B8	1st/2nd	included

socomec
Innovative Power Solutions

Terminal shrouds

Use
Protection against direct contact with terminals or connecting parts.

Advantage
Perforations allow remote thermographic inspection without the need to remove the shrouds.

acces_206_a_2_cat

Rating (A)	Frame size	No. of poles	Position	Reference
125 … 200	B3	3 P	top / bottom / front (I) / rear (II)	2694 **3014**(1)(2)
125 … 200	B3	4 P	top / bottom / front (I) / rear (II)	2694 **4014**(1)(2)
250 … 400	B4	3 P	top / bottom / front (I) / rear (II)	2694 **3021**(1)(2)
250 … 400	B4	4 P	top / bottom / front (I) / rear (II)	2694 **4021**(1)(2)
500 … 630	B5	3 P	top / bottom / front (I) / rear (II)	2694 **3051**(1)(2)
500 … 630	B5	4 P	top / bottom / front (I) / rear (II)	2694 **4051**(1)(2)

(1) To shroud front switch top and bottom 4 references required for a SIRCOVER and 6 references for a SIRCOVER Bypass.
(2) To shroud front switch top and bottom 2 references required for a SIRCOVER and a SIRCOVER Bypass.

Terminal screens

Use
Top and bottom protection against direct contact with terminals or connection parts.

acces_207_a_2_cat

Rating (A)	Frame size	No. of poles	Position	Reference
125 … 200	B3	3 P	top / bottom	1509 **3012**
125 … 200	B3	4 P	top / bottom	1509 **4012**
250 … 400	B4	3 P	top / bottom	1509 **3025**
250 … 400	B4	4 P	top / bottom	1509 **4025**
500 … 630	B5	3 P	top / bottom	1509 **3063**
500 … 630	B5	4 P	top / bottom	1509 **4063**
800 … 1250	B6	3 P	top / bottom	1509 **3080**
800 … 1250	B6	4 P	top / bottom	1509 **4080**
1600	B7	3 P	top / bottom	1509 **3160**
1600	B7	4 P	top / bottom	1509 **4160**
2000 … 3200	B8	3 / 4 P	top / bottom	included

Inter-phase barrier

Use
Safety isolation between the terminals, essential for use at 690 VAC or in a polluted or dusty atmosphere.

Rating (A)	Frame size	No. of poles	Reference
125 … 200	B3	2 P	2998 **0033**
125 … 200	B3	3 P	2998 **0034**
250 … 400	B4	2 P	2998 **0023**
250 … 400	B4	3 P	2998 **0024**
500 … 630	B5	2 P	2998 **0013**
500 … 630	B5	3 P	2998 **0014**
800 … 3200	B6 … B8	2/3 P	**included**

Accessories (continued)

Key handle interlocking system

Padlocking in position I, 0 or II

SIRCOVER Rating (A) / Frame size	SIRCOVER Bypass Rating (A) / Frame size	Operation	Figure	Reference
125 … 630 / B3 ... B5	125 … 200 / B3	external	1	1423 **2813**

Locking using RONIS EL11AP lock in position 0 (not included)

SIRCOVER Rating (A) / Frame size	SIRCOVER Bypass Rating (A) / Frame size	Operation	Figure	Reference
125 … 630 / B3 … B5	125 … 200 / B3	direct	2	4109 **1006**(1)
	250 … 630 / B4 ... B5	direct	3	please consult us
800 … 1600 / B6 … B7	800 … 1600 / B6 ... B7	direct	3	4109 **1004**(2)
2000 … 3200 / B8		direct	3	4109 **2007**(2)
125 … 630 / B3 … B5	125 … 630 / B3 … B5	external	4	1499 **7701**(2)
2000 … 3200 / B8	800 … 1600 / B6 … B7	external	4	2799 **7002**(2)

(1) Specific handle included.
(2) This locking facility can be configured by the user in the 3 positions.

Locking using RONIS EL11AP lock in position I, 0, II (not included)

SIRCOVER Rating (A) / Frame size	SIRCOVER Bypass Rating (A) / Frame size	Operation	Figure	Reference
125 … 630 / B3 … B5	125 … 200 / B3	direct	2	4109 **1002**(1)
	250 … 630 / B4 … B5	direct	3	please consult us
800 … 1600 / B6 … B7	800 … 1600 / B6 … B7	direct	3	4109 **1004**(2)
2000 … 3200 / B8		direct	3	4109 **2007**(2)
125 … 630 / B3 … B5	125 … 630 / B3 … B5	external	4	1499 **7701**(2)
2000 … 3200	800 … 1600 / B6 … B7	external	4	2799 **7002**(2)

(1) Specific handle included.
(2) This locking facility can be configured by the user in the 3 positions.

Locking using 230 VAC undervoltage coil in position (factory fitted)

SIRCOVER Rating (A) / Frame size	SIRCOVER Bypass Rating (A) / Frame size	Operation	Figure	Reference
800 … 3200 / B6 … B8	800 … 1600 / B6 … B7	direct	3	please consult us

Locking using K-type CASTELL lock (not supplied)

Rating (A) SIRCOVER Frame size	SIRCOVER Bypass Rating (A) / Frame size	Operation	Figure	Reference
125 … 1600 / B3 … B7	125 … 630 / B3 … B5	external	4	1499 **7702**
2000 … 3200 / B8	800 … 1600 / B6 … B7	external	4	2799 **7003**

Use

- Using padlock (not supplied). This device is factory mounted in the direct or external operation handle and allows the use of up to 3 padlocks.
- Locking:
  - using lock (not supplied)
  - using undervoltage coil.
- The interlocking positions are either determined as standard or configured by the user by removing the pre-formed tabs.
- Padlocking and locking can be combined.

Fig. 1

acces_061_a_1_x_cat

Fig. 2

acces_001_a_1_x_cat

Fig. 3

acces_132_a_1_x_cat

Fig.4

acces_158_a_1_x_cat

Other specific accessories

b4_03_04_01

- Customised protection screens (for specific dimensions or high ambient temperatures).
- Connection accessories.
- Low level auxiliary contacts.

socomec Innovative Power Solutions

Enclosed transfer switch solutions

General characteristics

- Adapted to mechanical risk and dust hazard.
- Operation handle: S-type black handle padlockable in position 0.
- Protection degree: IP54
- Colour: RAL 7035 up to 630 A, above RAL 7035 and RAL 9001 for casing and door.
- Cable gland plate: top and bottom
- Material: XC steel, thickness 1.5 mm.
- Coating: epoxy polyester powder (ratings < 630 A) , polyester powder (ratings ≥ 630 A)
- Wall mounting: 4 fixing lugs supplied loose.
- Door: solid with hinges.
- Door lock: 3 mm double bar key (ratings < 630 A), 8 mm square key (ratings ≥ 630 A), key supplied.
- Miscellaneous: 2 earth connection points, double door locking.

References

Rating (A)	Number of poles	Top/Bottom connection I - 0 - II Reference
125	3 P	4212 **3012**
125	4 P	4212 **4012**
160	3 P	4212 **3016**
160	4 P	4212 **4016**
250	3 P	4212 **3025**
250	4 P	4212 **4025**
400	3 P	4212 **3040**
400	4 P	4212 **4040**
500	3 P	4212 **3050**
500	4 P	4212 **4050**
630	3 P	4212 **3063**
630	4 P	4212 **4063**
800	3 P	4212 **3080**
800	4 P	4212 **4080**
1250	3 P	4212 **3120**
1250	4 P	4212 **4120**
1600	3 P	4212 **3160**
1600	4 P	4212 **4160**

coff_298_b

Dimensions

(1) 125 … 630 A: 58 mm
800 … 1600 A: 74 mm.

Rating (A)	No. of poles	H x W x D (mm)	Max. connection cross-section (mm²)	M (mm)	N (mm)	Z (mm)	Top/Bottom connection Ah (mm)	B1 (mm)	Weight (kg)
125	3/4 P	500 x 400 x 250	50	448	458	28	190	190	23
160	3/4 P	500 x 400 x 250	95	448	458	28	190	190	23
250	3/4 P	500 x 400 x 250	150	448	458	29.3	185	185	23
400	3/4 P	800 x 600 x 300	240	758	552	29.3	330	330	45
500	3/4 P	800 x 600 x 300	240	648	658	45	298	298	55
630	3/4 P	800 x 600 x 300	2 x 300	648	658	45	290	290	55
800	3/4 P	1200 x 700 x 500	2 x 300	740	1152	24	465	465	78
1 250	3/4 P	1200 x 700 x 500	4 x 185	740	1152	24	465	465	88
1 600	3/4 P	1200 x 700 x 500	4 x 300	740	1152		470	470	94

SIRCOVER AC - Characteristics according to IEC 60947-3 and IEC 60947-6-1

125 to 630 A / B3 to B5

Thermal current I_{th} at 40°C		125 A	160 A	200 A	250 A	315A	400 A	500 A	630 A
Frame size		**B3**	**B3**	**B3**	**B4**	**B4**	**B4**	**B5**	**B5**
Rated insulation voltage U_i (V)		800	800	800	1000	1000	1000	1000	1000
Rated impulse withstand voltage U_{imp} (kV)		8	8	8	12	12	12	12	12
Rated operational currents Ie (A) according to IEC 60947-6-1									
Rated voltage	**Utilisation category**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**
415 VAC	AC-31 A / AC-31 B	125	160	200	250	315	400	500	630
415 VAC	AC-32 A / AC-32 B				200	315	400	500	500
415 VAC	AC-33 A / AC-33 B				200	200	200	400	400
Rated operational currents I_e (A) according to IEC 60947-3									
Rated voltage	**Utilisation category**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**
415 VAC	AC-20 A / AC-20 B	125/125	160/160	200/200	250/250	315/315	400/400	500/500	630/630
415 VAC	AC-21 A / AC-21 B	125/125	160/160	200/200	250/250	315/315	400/400	500/500	630/630
415 VAC	AC-22 A / AC-22 B	125/125	160/160	200/200	250/250	315/315	400/400	500/500	630/630
415 VAC	AC-23 A / AC-23 B	125/125	160/160	200/200	200/200	315/315	400/400	500/500	630/630
500 VAC	AC-20 A / AC-20 B	125/125	160/160	200/200	250/250	315/315	400/400	500/500	630/630
500 VAC	AC-21 A / AC-21 B	125/125	160/160	200/200	250/250	315/315	400/400	500/500	630/630
500 VAC	AC-22 A / AC-22 B	125/125	160/160	200/200	200/250	200/315	200/400	500/500	500/500
500 VAC	AC-23 A / AC-23 B	80/80	80/80	80/80	200/200	200/200	200/200	400/400	400/400
690 VAC(7)	AC-20 A / AC-20 B	125/125	160/160	200/200	250/250	315/315	400/400	500/500	630/630
690 VAC(7)	AC-21 A / AC-21 B	125/125	160/160	200/200	200/200	200/200	200/200	500/500	500/500
690 VAC(7)	AC-22 A / AC-22 B	125/125	125/125	125/125	160/160	160/160	160/160	400/400	400/400
690 VAC(7)	AC-23 A / AC-23 B	63/80	63/80	63/80	125/125	125/125	125/125	400/400	400/400
220 VDC	DC-20 A / DC-20 B	125/125	160/160	200/200	250/250	315/315	400/400	500/500	630/630
220 VDC	DC-21 A / DC-21 B	125/125	160/160	200/200	250/250	250/250	250/250	500/500	630/630
220 VDC	DC-22 A / DC-22 B	125/125	160/160	200/200	250/250	250/250	250/250	500/500	630/630
220 VDC	DC-23 A / DC-23 B	125/125	125/125	125/125	200/200	200/200	200/200	500/500	630/630
440 VDC	DC-20 A / DC-20 B	125/125	160/160	200/200	250/250	315/315	400/400	500/500	630/630
440 VDC	DC-21 A / DC-21 B	125(2)/125(2)	125(2)/125(2)	125(2)/125(2)	200(2)/200(2)	200(2)/200(2)	200(2)/200(2)	500(2)/500(2)	630(2)/630(2)
440 VDC	DC-22 A / DC-22 B	125(2)/125(2)	125(2)/125(2)	125(2)/125(2)	200(2)/200(2)	200(2)/200(2)	200(2)/200(2)	500(2)/500(2)	630(2)/630(2)
440 VDC	DC-23 A / DC-23 B	125(3)/125(3)	125(3)/125(3)	125(3)/125(3)	200(3)/200(3)	200(3)/200(3)	200(3)/200(3)	500(3)/500(3)	500(3)/500(3)
Operational power in AC-23 (kW)									
At 400 VAC without pre-break in AC(3)		63/63	80/80	80/80	132/132	132/132	280/280	280/280	450/450
At 690 VAC without pre-break in AC(3)		55/75	55/75	55/75	90/110	90/110	150/185	150/185	185/220
Reactive power (kvar)									
At 415 VAC		55	75	90	115	145	185	230	290
Fuse protected short-circuit withstand as per IEC 60947-3 at 690 VAC									
Prospective short-circuit current (kA rms)		100 (5)	100 (5)	50 (5)	50	50	50	50	50
Associated fuse rating (A)		125	160	200	250	315	400	500	630
Circuit breaker protected short-circuit withstand with any circuit breaker that ensures tripping in less than 0.3s(4)									
Rated short-time withstand current 0.3s I_{cw} (kA rms)		12 (5)	12 (5)	12 (5)	15	15	15	17	17
Short-circuit withstand without protection as per IEC 60947-3 at 690 VAC									
Rated short-time withstand current 1s I_{cw} (kA rms)		7 (5)	7 (5)	7 (5)	8	8	8	10	10
Rated peak withstand current (kA peak)		20	20	20	30	30	30	45	45
Rated short-time withstand current 60ms I_{cw} (kA rms) as per IEC 60947-6-1 at 415 VAC					10 (6)	10 (6)	10 (6)	10	12.6
Connection									
Minimum Cu cable cross-section (mm²)		35	50	70	95	150	185	240	2 x 150
Minimum Cu busbar cross-section (mm²)									2 x 30 x 5
Maximum Cu cable cross-section (mm²)		50	95	120	150	240	240	2 x 185	2 x 300
Maximum Cu busbar width (mm)		25	25	25	32	32	32	50	50
Tightening torque mini / maxi (Nm)		9/13	9/13	9/13	20/26	20/26	20/26	20/26	20/26
Mechanical characteristics									
Durability (number of operating cycles)		10 000	10 000	10 000	8 000	8 000	5 000	5 000	5 000
Weight of 3 P switch (kg)		2.9	2.9	2.9	3.8	3.9	3.9	8.6	9.1
Weight of 4 P switch (kg)		4.1	4.1	4.1	4.6	4.9	4.9	10.4	11.1

(1) Category with index A = frequent operation - Category with index B = infrequent operation.
(2) 3-pole device with 2 pole in series for the "+" and 1 pole for the "-". 4-pole device with 2 poles in series by polarity.
(3) The power value is given for information only, the current values vary from one manufacturer to another.
(6) Value for coordination with any circuit-breaker that ensures tripping in less than 0.3s. For coordination with specific circuit-breaker references, higher short-circuit current values are available. Please consult us.
(5) Data at 415 VAC
(6) Data at 30ms
(7) With terminal shrouds or phase barrier.

socomec
Innovative Power Solutions

800 to 3200 A / B6 to B8

Thermal current I_{th} at 40°C		800 A	1000 A	1250 A	1600 A	2000 A	2500 A	3200 A
Frame size		**B6**	**B6**	**B6**	**B7**	**B8**	**B8**	**B8**
Rated insulation voltage U_i (V)		1000	1000	1000	1000	1000	1000	1000
Rated impulse withstand voltage U_{imp} (kV)		12	12	12	12	12	12	12
Rated operational currents I_e (A) according to IEC 60947-6-1								
Rated voltage	**Utilisation category**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**
415 VAC	AC-31 A / AC-31 B	800	1000	1250	1600	2000	2500	3200
415 VAC	AC-32 A / AC-32 B	800	1000	1250	1600	2000	2000	2000
415 VAC	AC-33 A / AC-33 B	800	800	800	1000	1250	1250	1250
Rated operational currents I_e (A) according to IEC 60947-3								
Rated voltage	**Utilisation category**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**
415 VAC	AC-20 A / AC-20 B	800/800	1000/1000	1250/1250	1600/1600	2000/2000	2500/2500	3200/3200
415 VAC	AC-21 A / AC-21 B	800/800	1000/1000	1250/1250	1600/1600	-/2000	-/2500	-/3200
415 VAC	AC-22 A / AC-22 B	800/800	1000/1000	1250/1250	1600/1600	-/2000	-/2500	-/3200
415 VAC	AC-23 A / AC-23 B	800/800	1000/1000	1250/1250	1250/1250	-/1600	-/1600	-/1600
500 VAC	AC-20 A / AC-20 B	800/800	1000/1000	1250/1250	1600/1600	2000/2000	2500/2500	3200/3200
500 VAC	AC-21 A / AC-21 B	800/800	1000/1000	1250/1250	1600/1600	-/2000	-/2500	-/3200
500 VAC	AC-22 A / AC-22 B	630/630	800/800	1000/1000	1600/1600			
500 VAC	AC-23 A / AC-23 B	400/400	630/630	800/800	1000/1000			
690 VAC(6)	AC-20 A / AC-20 B	800/800	1000/1000	1250/1250	1600/1600	2000/2000	2500/2500	3200/3200
690 VAC(6)	AC-21 A / AC-21 B	800/800	1000/1000	1250/1250	1600/1600	-/2000	-/2500	-/3200
690 VAC(6)	AC-22 A / AC-22 B	630/630	800/800	1000/1000	1000/1000			
690 VAC(6)	AC-23 A / AC-23 B	400/400	630/630	800/800	800/800			
220 VDC	DC-20 A / DC-20 B	800/800	1000/1000	1250/1250	1600/1600			
220 VDC	DC-21 A / DC-21 B	800/800	1000/1000	1250/1250	1250/1250			
220 VDC	DC-22 A / DC-22 B	800/800	1000/1000	1250/1250	1250/1250			
220 VDC	DC-23 A / DC-23 B	800/800	1000/1000	1250/1250	1250/1250			
440 VDC	DC-20 A / DC-20 B	800/800	1000/1000	1250/1250	1600/1600			
440 VDC	DC-21 A / DC-21 B	800(3)/800(3)	1000(3)/1000(3)	1250(3)/1250(3)	1250/1250			
440 VDC	DC-22 A / DC-22 B	800(3)/800(3)	1000(3)/1000(3)	1250(3)/1250(3)	1250/1250			
440 VDC	DC-23 A / DC-23 B	800(3)/800(3)	1000(3)/1000(3)	1250(3)/1250(3)	1250/1250			
Operational power in AC-23 (kW)								
At 400 VAC without pre-break in AC(3)		710/710	710/710	710/710	710/710	710/710		
At 690 VAC without pre-break in AC(3)		185/220	475/475	475/475	750/750	750/750		
Reactive power (kvar)								
At 400 VAC (5)		365	460	575				
Fuse protected short-circuit withstand as per IEC 60947-3 at 415 VAC								
Prospective short-circuit current (kA rms)		50	100	100	100			
Associated fuse rating (A)		800	1000	1250	2 x 800			
Circuit breaker protected short-circuit withstand with any circuit breaker that ensures tripping in less than 0.3s(4)								
Rated short-time withstand current 0.3s I_{cw} (kA rms)		47	64	64	78	78	78	78
Short-circuit withstand without protection as per IEC 60947-3 at 415 VAC								
Rated short-time withstand current 1s I_{cw} (kA rms)		26	35	35	50	50	50	50
Rated peak withstand current (kA peak)		55	55	80	110	110	110	120
Rated short-time withstand current 60ms Icw (kA rms) as per IEC 60947-6-1 at 415 VAC		16	20	25	32	40	50	50
Connection								
Minimum Cu cable cross-section (mm^2)		2 x 185	2 x 240					
Minimum Cu busbar cross-section (mm^2)		2 x 40 x 5	2 x 50 x 5	2 x 60 x 5	2 x 80 x 5	2 x 100 x 10	2 x 100 x 10	2 x 100 x 10
Maximum Cu cable cross-section (mm^2)		2 x 300	4 x 185	4 x 185	6 x 185			
Maximum Cu busbar width (mm)		63	63	63	100	100	100	100
Tightening torque min (Nm)		20/26	20/26	20/26	40/45	40/45	40/45	40/45
Mechanical characteristics								
Durability (number of operating cycles)		4 000	4 000	4 000	3 000	3 000	3 000	3 000
Weight of a 3 pole device (kg)		20.5	21.0	21.6	25.7	42.0	42.0	52.3
Weight of a 4 pole device (kg)		24.8	25.6	26.2	32.0	52.9	52.9	66.6

(1) Category with index A = frequent operation - Category with index B = infrequent operation.
(2) 3-pole device with 2 pole in series for the "+" and 1 pole for the "-". 4-pole device with 2 poles in series by polarity.
(3) The power value is given for information only, the current values vary from one manufacturer to another.
(6) Value for coordination with any circuit-breaker that ensures tripping in less than 0.3s. For coordination with specific circuit-breaker references, higher short-circuit current values are available. Please consult us.
(5) Data at 415 VAC.
(6) With terminal shrouds or phase barrier.

Dimensions

125 to 1600 A / B3 to B7

Direct front operation

A. S2 type handle for external operation: 125 to 630 A
B. S4 type handle for external operation: 800 to 1600 A

External front operation

1. Terminal shrouds
2. Direct handle operation:
- 125 to 630 A: L1 = 140 mm,
- 800 to 1600 A: L1 = 210 mm.

Rating (A)/ Frame size	Overall dimensions A 3p.	A 4p.	C	E min	Terminal shrouds AC	Switch body H	HA	J 3p.	J 4p.	Switch mounting M 3p.	M 4p.	N	Connection T	U	V	W	X 3p.	X 4p.	Y	Z	Z1	AA	BA	CA
125 / B3	221	251	218	208 … 436	235	148	25	182	212	156	186	101	36	20	25	8.5	56	50	3.5	28	124	135	115	10
160 / B3	221	251	218	208 … 436	235	148	25	182	212	156	186	101	36	20	25	8.5	56	50	3.5	28	124	135	115	10
200 / B3	221	251	218	208 … 436	235	148	25	182	212	156	186	101	36	20	25	8.5	56	50	3.5	28	124	135	115	10
250 / B4	262	312	218	208 … 436	280	148	25	223	273	196	246	116	50	25	30	11	61	61	3.5	30	124	160	130	15
315 / B4	262	312	218	208 … 436	280	148	25	223	273	196	246	116	50	35	35	11	61	61	3.5	30	124	170	140	15
400 / B4	262	312	218	208 … 436	280	148	25	223	273	196	246	116	50	35	35	11	61	61	3.5	30	124	170	140	15
500 / B5	319	379	295	285 … 513	401	225	25	272	332	246	306	176	65	32	37	13	70.5	65.5	5	43	180	235	205	15
630 / B5	319	379	295	285 … 513	400	225	25	272	332	246	306	176	65	45	50	13	70.5	65.5	5	43	180	260	220	20
800 / B6	386	466	375	425 … 577	459	298	29	306.5	386.5	255	336	250	80	50	60.5	15	48	48	7	66.5	253.5	321		26.5
1000 / B6	386	466	375	425 … 577	459	298	29	306.5	386.5	255	336	250	80	50	60.5	15	48	48	7	66.5	253.5	321		26.5
1250 / B6	386	466	375	425 … 577	459	298	29	306.5	386.5	255	336	250	80	60	65	16x11	48	48	7	66.5	255.5	330		29.5
1600 / B7	478	598	375	425 … 577	461	298	29	388.5	518.5	347	467	250	120	90	43.5	12.5x5	54	54	8	66.5	255.5	288		15

SIRCOVER 2000 à 3200 A / B8

Direct front operation

Rating (A) / Frame size	Overall dimensions A 3p.	A 4p.	Switch mounting M 3p.	M 4p.
2000 … 3200 / B8	478	598	347	467

SIRCOVER Bypass 125 to 1600 A / B3 to B7

Direct front operation

External front operation

svr_070_j_1_x_cat

A. S2 type handle for external operation: 125 to 200 A
B. S3 type handle for external operation: 250 to 630 A
C. External double lever handle: 800 to 1600 A

1. Terminal shrouds
2. Direct handle operation:
- 125 to 200 A: L1 = 140 mm,
- 250 to 630 A: L1 = 210 mm,
- 800 to 1600 A: L1 = Ø 330 mm.

Rating (A) / Frame size	Overall dimensions				Terminal shrouds	Switch body				Switch mounting			Connection												
	A 3+6p.	A 4+8p.	C	E min	AC	H	HA	J 3+6 p.	J 4+8 p.	M 3+6 p.	M 4+8 p.	N	T	U	V	W	X 3+6p.	X 4+8p.	Y	Z	Z1	Z1	AA	BA	CA
125 / B3	221	251	313	320	235	243	25	182	212	156	186	101	36	20	25	8.5	56	50	3.5	28	124	219	135	115	10
160 / B3	221	251	313	320	235	243	25	182	212	156	186	101	36	20	25	8.5	56	50	3.5	28	124	219	135	115	10
200 / B3	221	251	313	320	235	243	25	182	212	156	186	101	36	20	25	8.5	56	50	3.5	28	124	219	135	115	10
250 / B4	262	312	313	298	280	243	25	223	273	196	246	116	50	25	30	11	61	61	3.5	30	124	219	160	130	10
400 / B4	262	312	313	298	280	243	25	223	273	196	246	116	50	35	35	11	61	61	3.5	30	124	219	170	140	15
500 / B5	319	379	432	417	401	362	25	272	332	246	306	176	65	32	37	13	70.5	65.5	5	43	180	317	235	205	15
630 / B5	319	379	432	417	400	362	25	272	332	246	306	176	65	45	50	13	70.5	65.5	5	43	180	317	260	220	20
800 / B6	386	466	560	550	459	479	29	306.5	386.5	255	335	250	80	50	60.5	15	48	48	7	66.5	253.5	439.5	321		26.5
1250 / B6	386	466	560	550	459	479	29	306.5	386.5	255	335	250	80	60	65	16x11	48	48	7	66.5	253.5	439.5	320		29.25
1600 / B7	478	598	560	550	461	479	29	388.5	518.5	347	467	250	120	90	43.5	12.5x5	54	54	8	66.5	253.5	439.5	288		15

Connection terminals

SIRCOVER and SIRCOVER Bypass 800 A / B6

svr_077_a_1_x_cat

SIRCOVER and SIRCOVER Bypass 1250 A / B6

svr_078_b_1_x_cat

SIRCOVER 1600 to 3200 A / B7 to B8 SIRCOVER Bypass 1600 A / B7

svr_098_a_1_x_cat

Dimensions for external handles

SIRCOVER 125 to 630 A / B3 to B5

Handle type	Direction of operation	Front operation – Door drilling	
		With lock RONIS EL11AP	With lock CASTELL K
S2 type	0 or I+II		

(1) Ø31 to Ø37: Rear screw mounting Ø37: front clip mounting.

poign_030_a_1_gb_cat

SIRCOVER 800 to 1600 A / B6 to B7

Handle type	Direction of operation	Front operation – Door drilling	
		With lock RONIS EL11AP	With lock CASTELL K
S4 type	0 or I+II		

(1) Ø31 to Ø37: Rear screw mounting Ø37: front clip mounting.
(2) Ø6 to Ø7: clip mounting.

poign_031_a_1_gb_cat

SIRCOVER 2000 to 3200 A / B8

Handle type	Front operation – Direction of operation	Door drilling	
			With lock CASTELL K
S5 type with V Escutcheon			

poign_023_a_1_gb_cat

socomec Innovative Power Solutions

SIRCOVER Bypass 125 to 200 A / B3

Handle type	Front operation Direction of operation	Door drilling	
S2 type		With lock RONIS EL11AP	With lock CASTELL K

poign_032_a_1_gb_cat

(1) Ø31 to Ø37: Rear screw mounting Ø37: front clip mounting.

SIRCOVER Bypass 250 to 630 A / B4 to B5

Handle type	Front operation Direction of operation	Door drilling	
S3 type		With lock RONIS EL11AP	With lock CASTELL K

poign_033_a_1_gb_cat

(1) Ø31 to Ø37: Rear screw mounting Ø37: front clip mounting.

SIRCOVER Bypass 800 to 1600 A / B6 to B7

Handle type	Front operation Direction of operation	Door drilling	
C type			With lock CASTELL K

poign_022_a_1_gb_cat

SIRCOVER ATS Bypass

Manual transfer switches
from 125 to 1600 A

svr_133_a

SIRCOVER ATS Bypass
I-0-II 12+4P

The solution for

- Industry
- Healthcare buildings

Strong points

- Stable positions
- Secured breaking
- On load switching
- A complete solution

Conformity to standards

- IEC 60947-3

Function

SIRCOVER ATS Bypass switches are manual four pole transfer switches with positive break indication. They are designed to isolate ATS type electrical equipment (automatic transfer switch) or UPS, with minimum interruption to the load supply. Integrating a SOCOMEC transfer switch into the installation enables source selection when in Bypass (see operating principle below).

Advantages

Stable positions
SIRCOVER ATS Bypass switches have 3 stable positions which are not affected by voltage drops or vibrations.

On load switching
Thanks to its AC-22 characteristics, tested in accordance with standard IEC 60947-3, the SIRCOVER ATS Bypass enables on load switching.

Secured breaking
Simultaneous upstream and downstream isolation and fully visualised breaking.

A complete solution
The SIRCOVER ATS Bypass is a single product offering a genuine solution incorporating both an equipment isolation function and a switching function.

Operating principle

atys_569_d_1_gb_cat

In Bypass position:
- Without SIRCOVER: The load is supplied directly by one of the two power sources (transformer T1 for example).
- With a SIRCOVER: The supply source can be selected.

socomec Innovative Power Solutions

References

Rating (A)	No. of poles	Switch body	Direct handle	External handle	Shaft for external handle	Bridging bars	Auxiliary contact	Terminal shrouds	Terminal screens
125 A	12 + 4 P	4100 **9813**	S3 type Black IP65 I - O - II 1433 **3113**	S3 type Black IP65 I - O - II 1433 **3113**	200 mm 1401 **1520**	4 P 4109 **4019**	1st contact NO/NC included 2nd contact NO/NC 4109 **0021**(1)	4 P 2694 **4014** (2)(3)	4 P 1509 **4012**(4)
160 A	12 + 4 P	4100 **9816**							
250 A	12 + 4 P	4100 **9825**			320 mm 1401 **1532**	4 P 4109 **4025**			
400 A	12 + 4 P	4100 **9840**			400 mm 1401 **1540**	4 P 4109 **4039**		4 P 2694 **4021**(2)(3)	4 P 1509 **4025**(4)
630 A	12 + 4 P	4100 **9863**				4 P 4109 **4063**		4 P 2694 **4051** (2)(3)	4 P 1509 **4063**(4)
800 A	12 + 4 P	4100 **9880**	Black 2799 **7062**	Black IP65 I - 0 - II 2799 **7147**	Included with the external handle	4 P 4109 **4080**		Please consult us	4 P 1509 **4080**(4)
1000 A	12 + 4 P	4100 **9881**							
1250 A	12 + 4 P	4100 **9882**				4 P 4109 **4160**			
1600 A	12 + 4 P	4100 **9886**							

(1) 2 pieces: one for position I and one for position II.
(2) To fully shroud front, rear, top and bottom 8 references required.
(3) To shroud front switch top and bottom 4 references required.
(4) For complete front protection, order the reference twice.

Accessories

Key handle interlocking system

Locking in position 0 with RONIS EL11AP (lock not supplied)

Rating (A)	Operation	Figure	Reference
125 … 630	direct	1	4109 **1006** (1)
125 … 630	external	3	1499 **7701**
800 … 1600	direct and external	2	Please consult us

(1) Specific handle included.

Locking in positions I, 0, II with RONIS EL11AP (lock not supplied)

Rating (A)	Operation	Figure	Reference
125 … 630	direct	1	4109 **1002** (1)
800 … 1600	direct	2	Please consult us

(1) Specific handle included.

Locking with CASTELL K type lock (lock not supplied)

Rating (A)	Operation	Figure	Reference
125 … 630	external	3	1499 **7702**
800 … 1600	external		Please consult us

Fig. 1

acces_001_a_1_x_cat

Fig.2

acces_122_a_1_x_cat

Fig. 3

acces_158_a_1_x_cat

Characteristics according to IEC 60947-3

125 to 1600 A

Thermal current I_{th} at 40°C		125 A	160 A	250 A	400 A	630 A	800 A	1000 A	1250 A	1600 A
Rated insulation voltage U_i (V)		800	800	800	800	1000	1000	1000	1000	1000
Rated impulse withstand voltage U_{imp} (kV)		8	8	8	8	12	12	12	12	12
Rated operational currents I_e (A)										
Rated voltage	**Utilisation category**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**	**A/B(1)**
415 VAC	AC-20 A / AC-20 B	125/125	160/160	250/250	400/400	630/630	800/800	1000/1000	1250/1250	1600/1600
415 VAC	AC-21 A / AC-21 B	125/125	160/160	250/250	400/400	630/630	800/800	1000/1000	1250/1250	1600/1600
415 VAC	AC-22 A / AC-22 B	125/125	160/160	250/250	400/400	630/630	800/800	1000/1000	1250/1250	1600/1600
415 VAC	AC-23 A / AC-23 B	125/125	160/160	250/250	250/250	500/500	800/800	1000/1000	1250/1250	1250/1250
690 VAC(2)	AC-20 A / AC-20 B	125/125	160/160	250/250	400/400	630/630	800/800	1000/1000	1250/1250	1600/1600
690 VAC(2)	AC-21 A / AC-21 B	125/125	160/160	200/250	200/250	500/500	800/800	800/800	800/800	1000/1000
690 VAC(2)	AC-22 A / AC-22 B	125/125	125/125	125/160	125/160	315/315	800/800	800/800	800/800	1000/1000
690 VAC(2)	AC-23 A / AC-23 B	63/80	63/80	100/125	100/125	160/200	200/250	200/250	200/250	500/500
220 VDC	DC-20 A / DC-20 B	125/125	160/160	250/250	400/400	630/630	800/800	1000/1000	1250/1250	1600/1600
220 VDC	DC-21 A / DC-21 B	125/125	160/160	250/250	250/250	630/630	800/800	1000/1000	1250/1250	1250/1250
220 VDC	DC-22 A / DC-22 B	125/125	160/160	250/250	250/250	500/500	800/800	1000/1000	1250/1250	1250/1250
220 VDC	DC-23 A / DC-23 B	125/125	125/125	200/200	200/200	500/500	800/800	1000/1000	1250/1250	1250/1250
440 VDC	DC-20 A / DC-20 B	125/125	160/160	250/250	400/400	630/630	800/800	1000(4)/1000(4)	1250/1250	1600/1600
440 VDC	DC-21 A / DC-21 B	125(3)/125(3)	125(3)/125(3)	200(3)/200(3)	200(3)/200(3)	500(3)/500(3)	800(4)/800(4)	1000(4)/1000(4)	1250(4)/1250(4)	1250(4)/1250(4)
440 VDC	DC-22 A / DC-22 B	125(3)/125(3)	125(3)/125(3)	200(3)/200(3)	200(3)/200(3)	500(3)/500(3)	800(4)/800(4)	1000(4)/1000(4)	1250(4)/1250(4)	1250(4)/1250(4)
440 VDC	DC-23 A / DC-23 B	125(4)/125(4)	125(4)/125(4)	200(4)/200(4)	200(4)/200(4)	500(4)/500(4)	800(4)/800(4)	1000(4)/1000(4)	1250(4)/1250(4)	1250(4)/1250(4)
Operational power in AC-23 (kW)										
At 400 VAC without pre-break in AC(1)(5)		63/63	80/80	132/132	132/132	280/280	450/450	710/710	710/710	710/710
At 690 VAC without pre-break in AC(1)(5)		55/75	55/75	90/110	90/110	150/185	185/220	185/220	185/220	475/475
Reactive power (kvar)										
At 400 VAC (5)		55	75	115	185	290	365	575	575	
Fuse protected short-circuit withstand (kA rms prospective)										
Prospective short-circuit (kA rms)(6)		100	100	50	18	70	50	100	100	100
Associated fuse rating (A)(6)		125	160	250	400	630	800	1000	1250	2 x 800
Circuit breaker protected short-circuit withstand with any circuit breaker that ensures tripping in less than 0.3s(7)										
Rated short-time withstand current 0.3s Icw (kA rms)		15	15	17	17	25	50	65	65	100
Short-circuit capacity (without protection)										
Thermal current I_{th} at 40°C		125 A	160 A	250 A	400 A	630 A	800 A	1000 A	1250 A	1600 A
Rated short-time withstand current 1s Icw (kA rms)		8	8	9	9	14	27	36	36	50
Rated short-circuit making capacity									75	75
Connection										
Minimum Cu cable cross-section (mm²)		35	50	95	185	2 x 150	2 x 185			
Minimum Cu busbar cross-section (mm²)						2 x 30 x 5	2 x 40 x 5	2 x 60 x 5	2 x 60 x 5	2 x 80 x 5
Maximum Cu cable cross-section (mm²)			50	95	150	240	2 x 300	2 x 300	2 x 300	4 x 185
Maximum Cu busbar width (mm)		25	25	32	32	50	63	63	63	100
Tightening torque min (Nm)		9	9	20	20	20	20	20	20	40
Mechanical characteristics										
Durability (number of operating cycles)		10000	10000	10000	10000	5000	3000	3000	3000	3000
Weight of 3 P switch (kg)		8.3	8.3	10	10.3	20.7	44.3	45.4	46.4	54.7
Weight of 4 P switch (kg)		10.6	10.6	11.7	12.4	24.8	53	54.4	55.8	67.3

(1) Category with index A = frequent operation
Category with index B = infrequent operation.
(2) With terminal shrouds.
(3) 3-pole device with 2 poles in series for the "+" and 1 pole for the "-".
(4) 4-pole device with 2 poles in series per polarity.
(5) The power value is given for information only, the current values vary from one manufacturer to another.
(6) For a rated operational voltage U_e = 400 VAC.
(7) Value for coordination with any circuit breaker that ensures tripping in less than 0.3s. For coordination with specific circuit-breaker references, higher short-circuit current values are available. Please consult us.

Connection terminals

SIRCOVER ATS Bypass 800 to 1000 A

SIRCOVER ATS Bypass 1250 to 1600 A

socomec Innovative Power Solutions

Dimensions

SIRCOVER ATS Bypass 125 to 630 A

Direct front operation

External front operation

A. S3 type handle for external front operation: 125 to 630 A.
1. Max length with shaft extension: E min + 50 mm.

Rating (A)	Overall dimensions A 8p.	E min	Switch body H	J 8p.	J1 8p.	Switch mounting M 8p.	N	Connection T	U	V	W	X 8p.	Y	Z	Z1	AA	BA	AC
125	610	260±1	193	238	338	576	101	36	20	25	8.5	76	3.5	47	143	135	115	10
160	610	260±1	193	238	338	576	101	36	20	25	8.5	76	3.5	47	143	135	115	10
250	725	260±1	193	295	396	691	116	50	25	30	11	83.5	3.5	49	143	160	130	10
400	725	260±1	193	295	396	691	116	50	35	35	11	83.5	3.5	49	143	170	140	15
630	850	337±1	270	358	458	816	176	65	45	50	13	91.5	5	62	199	235	220	20

SIRCOVER ATS Bypass 800 to 1600 A

Direct front operation

External front operation

Rating (A)	Overall dimensions A 8p.	Switch body J 8p.	J1 8p.	Switch mounting M 8p.	Connection T	V	X 8p.	Y	Z	AA	BA	AC
800	1 055	510.5	189	1 021	80	60.5	81.5	7	84.5	321	268	26.5
1000	1 055	510.5	189	1 021	80	60.5	81.5	7	84.5	321	268	26.5
1250	1 320	643	195	1 286	120	44	88	8	85.5	288	258	15
1600	1 320	643	195	1 286	120	44	88	8	85.5	288	258	15

Dimensions for external handles

SIRCOVER ATS Bypass 125 to 630 A

Handle type	Front operation: Direction of operation	Front operation: Door drilling
S3 type		

SIRCOVER ATS Bypass 800 to 1600 A

Handle type	Front operation: Direction of operation	Front operation: Door drilling
V type		