



Features:

- **Original**
 - Auto adjust the frame resource to it connected video
 - All channel synchronous playback
 - Support IE, Chrome, Firefox, Safari, and browser plug-in free
 - All channel synchronous live view and playback by smart phone
- **HD Input & Output**
 - H.264 video formats
 - Up to 4 1080P AHD / Analog camera can be accessed
 - HDMI / VGA at up to 1080P
- **HD Storage & Communication**
 - 1 HDD supported, Up to 8TB for each
 - 1 self-adaptive 10/100Mbps RJ45 interface
- **Special**
 - Auto record when camera be connected



GE-AVR7104H

Specifications

Model		GE-AVR7104H
Video / Audio input	AHD video input	4 channel AHD / Analog, 1080P30, 1080P25, 720P30, 720P25, 960H
	Supported camera types	AHD, 720P30, 720P25, 960H
	Audio input	2 channel
		RCA interface (2.0Vp-p, 1KΩ)
Video / Audio output	HDMI / VGA output	1080p (1920×1080)/60Hz, 720p (1280×720)/60Hz, UXGA (1600×1200)/60Hz, 1280×1024/60Hz
	Audio output	RCA (Linear, 1KΩ)
Video / Audio codec	Video compression	H.264
	Dual-stream	Support
	Encoding resolution	1080P (1920×1080), 720P (1280×720), 960H, D1
	Frame rate	60fps
	Audio compression	G.711u
	Synchronous playback	All channel synchronous playback
HDD	SATA	1 × SATA interface for 1 HDD
	Capacity	Up to 8TB capacity for each HDD
External interface	Network	1× 10/100Mbps self-adaptive RJ45 interface
	USB	Rear panel: 2× USB2.0
	Alarm	4 in / 1 out
	RS-485	N/A
	e-SATA	N/A
General	Power supply	12V 24W
	Operating condition	-10°C – 55°C (14°F – 131°F), Humidity 10 - 90%
	Dimensions (W×D×H)	380×290×45mm (15"×11.4"×1.8")