



Features:

- Original**
 - Auto adjust the frame resource to it connected video
 - All channel synchronous playback
 - Support IE, Chrome, Firefox, Safari, and browser plug-in free
 - All channel synchronous live view and playback by smart phone
- HD Input & Output**
 - H.264 video formats
 - Up to 16 720P AHD camera can be accessed
 - HDMI / VGA at up to 1080P
- HD Storage & Communication**
 - 2 HDDs supported, Up to 8TB for each
 - 1 self-adaptive 10/100Mbps RJ45 interface
- Special**
 - Auto record when camera be connected



GE-AVR7216

Specifications

Model		GE-AVR7216
Video / Audio input	AHD video input	16 channel BNC interface (1.0Vp-p, 75Ω)
	Supported camera types	AHD, 720P30, 720P25, 960H
	Audio input	2 channel RCA interface (2.0Vp-p, 1KΩ)
		HDMI / VGA output
Video / Audio output	Audio output	RCA (Linear, 1KΩ)
	Video / Audio codec	Video compression
Dual-stream		Support
Encoding resolution		720P (1280×720)
Frame rate		300fps
Audio compression		G.711u
Synchronous playback		All channel synchronous playback
HDD	SATA	2 × SATA interface for 2 HDD
	Capacity	Up to 8TB capacity for each HDD
External interface	Network	1× 10/100Mbps self-adaptive RJ45 interface
	USB	Rear panel: 2× USB2.0
	Alarm	4 in / 1 out
	RS-485	1× RS485 interface
	e-SATA	N/A
General	Power supply	12V 40W
	Operating condition	-10°C – 55°C (14°F – 131°F), Humidity 10 - 90%
	Dimensions (W×D×H)	440×301.5×70.1mm (17.3"×11.8"×2.7")