



Features:

Original

- Auto adjust the frame resource to it connected video
- All channel synchronous playback
- Support IE, Chrome, Firefox, Safari, and browser plug-in free
- All channel synchronous live view and playback by smart phone

HD Input & Output

- H.264 video formats
- 16 1080P AHD / Analog camera can be accessed
- HDMI / VGA at up to 1080P

HD Storage & Communication

- 2 HDD supported, Up to 8TB for each
- 1 self-adaptive 10/100Mbps RJ45 interface

Special

- Auto record when camera be connected



GE-AVR7416H

Specifications

Model		GE-AVR7416H
Video / Audio input	AHD video input	16 channel BNC interface (1.0Vp-p, 75Ω)
	Supported camera types	AHD / Analog, 1080P30, 1080P25, 720P30, 720P25, 960H
	Audio input	2 channel RCA interface (2.0Vp-p, 1KΩ)
		HDMI / VGA output
Video / Audio output	Audio output	RCA (Linear, 1KΩ)
	Video / Audio codec	Video compression
Dual-stream		Support
Encoding resolution		1080P (1920×1080), 720P (1280×720), 960H, D1
Frame rate		240fps
Audio compression		G.711u
Synchronous playback		All channel synchronous playback
HDD	SATA	4 × SATA interface for 2 HDD
	Capacity	Up to 8TB capacity for each HDD
External interface	Network	1× 10/100Mbps self-adaptive RJ45 interface
	USB	Rear panel: 2× USB2.0
	Alarm	4 in / 1 out
	RS-485	1× RS485 interface
	e-SATA	N/A
General	Power supply	12V 90W
	Operating condition	-10°C – 55°C (14°F – 131°F), Humidity 10 - 90%
	Dimensions (W×D×H)	380×290×45mm (15"×11.4"×1.8")