

GE-HSW238-IR


4MP AHD Analogue Bullet



Key features

- 1/2.9" Sony Progressive Scan CMOS
- 2.8-12mm, 12mm/16mm Optional
- Motorized Lens Optional
- Video Transmission 300m
- IR Up to 35m
- 2D DNR, dWDR, ICR
- Support AHD/TVI/CVI/CVBS Hybrid Output

Dimension



Accessories



CAMERA	
Image Sensor	1/3" CMOS
Signal System	PAL/NTSC
Min. illumination	Color:0.01Lux@(F1.2,AGC ON) ; B/W:0Lux@(IR LED ON)
S/N Ratio	≥48dB(min)(AGC closed)
Day & Night	ICR (Auto, Color, B/W, Ext)
Shutter Speed	PAL:1/50-1/50000, NTSC:1/60-1/60000
Wide Dynamic Range	dWDR
Digital Noise Reduction	Auto/Manual (1-10)
Lens	3.6mm
FOV	85°
IR LED	18pcs
IR Wavelength	850nm
IR Range	Up to 20m
Optional	Optional
Support	Support
IMAGE	
Effective Resolution	2560x1440
Frame	PAL:25fps, NTSC:30fps
Mirror	Support
White Balance	ATW/MWB
HLC	N/A
Privacy Masking	N/A
Language	English, Chinese
Motion Detection	N/A
VIDEO OUTPUT	
Max Distance	75-5 300m
Video Output	AHD/TVI/CVI/CVBS
GENERAL	
Power Supply	DC12V±10%
Power Consumption	4W(Max)
Operating Temperature	-10°C ~ 55°C (14°F ~ 131°F)
Operating Humidity	0% - 85% RH
Ingress Protection	Ip66
Approvals	CE/FCC
Product Dimensions	Φ94x84mm
Product Weight	360g