



Features:

- HD Input & Output: H.265 / H.264 video formats
- Up to 9 8MP IP camera can be accessed
- Video out: 1 VGA (Max. 1920 x 1080) / 1 HDMI (Max. 3840 x 2160)
- 1 HDD supported, Up to 8TB for each
- Support: 1 USB 2.0 interface, 1 USB 3.0 interface
- full channel realtime playback
- Perform 5 functions simultaneously: live view, recording, viewing over the network, data backup and playback viewing
- Multiple recording modes: continuous recording, scheduled recording, recording when motion or alarm
- Free Domain (free DDNS): multi-super.ddns.com, declared directly on the recorder
- Support the privacy masking function and motion detection
- Network: RJ45: 10/100/1000M, NTP, PPPoE, UPNP, FPT, Alarm Server, CGI, RTSP, RTMP
- Professional CMS: Unlimited registration recorder, 100 cameras simultaneously display.
- Support remote viewing by smart phone: Realview, Realview Pro
- Support ONVIF. Integrated Projects (up to 6 kV)



GE-NVR7109P

Specifications

| Model | | GE-NVR7109P |
|----------------------|------------------------|---|
| Video / Audio input | IP video input | 9 channel |
| | | BNC interface (1.0Vp-p, 75Ω) |
| | Supported camera types | AHD / Analog, 1080P30, 1080P25, 720P30, 720P25, 960H |
| | Audio input | 2 Ch. |
| | | RCA interface (2.0Vp-p, 1KΩ) |
| Video / Audio output | HDMI / VGA output | 1080p (1920×1080)/60Hz, 720p (1280×720)/60Hz, UXGA (1600×1200)/60Hz, 1280×1024/60Hz |
| | Audio output | RCA (Linear, 1KΩ) |
| Video / Audio codec | Video compression | H.265 |
| | Dual-stream | Support |
| | Encoding resolution | 1080H (960×1080), 720P (1280×720), 960H, D1 |
| | Frame rate | 120fps |
| | Audio compression | G.711u |
| | Synchronous playback | All channel synchronous playback |
| HDD | SATA | 1× SATA interface for 1 HDD |
| | Capacity | Up to 8TB capacity for each HDD |
| External interface | Network | 1× 10/100Mbps self-adaptive RJ45 interface |
| | USB | Rear panel: 2× USB2.0 |
| | Alarm | 2 in / 1 out |
| | RS-485 | N/A |
| | Model | N/A |
| General | Power supply | 12V 24W |
| | Operating condition | -10°C – 55°C (14°F – 131°F), Humidity 10 - 90% |
| | Dimensions (W×D×H) | 324×257×54mm |