



## Features:



**GE-NVR71664P**

- **Original**
  - SDA+ over LAN technology inside, One-click Access third-party
  - ONVIF camera
  - All channel real-time synchronous playback
  - Support IE, Chrome, Firefox, Safari, and browser plug-in free
  - All channel synchronous live view and playback by smart phone
- **HD Input & Output**
  - H.265 / H.264 video formats
  - Up to 64 8MP IP camera can be accessed
  - HDMI at up to 4K, VGA at up to 1080P
- **HD Storage & Communication**
  - 16 HDDs supported, Up to 8TB for each
  - 2 self-adaptive 10/100/1000M RJ45 interface
- **Special**
  - Instant playback for assigned channel during multi-channel live view mode
  - Smart search for selected area in the video, and smart playback to improve the efficiency
  - Support HDD quota and group mode
  - Support HDD hot swap

## Specifications

Model		GE-NVR71664P	
Video / Audio input	IP video input		64 channel Up to 12 MP for the first 4 Ch. , Up to 8MP for the rest
	File IP audio input		64 channel
	Two-way audio		1× RCA (2.0 Vp-p, 1 kΩ)
	Network	Incoming	Standard
Bandwidth			320Mbps
Outgoing		Standard	CGI, RTSP, RTMP(Only for H.264)
		Bandwidth	320Mbps
Video / Audio output	Recording resolution		Up to 12 MP for the first 4Channel, Up to 8MP for the rest
	HDMI output		4K (3840×2160)/60Hz, 1080p (1920×1080)/60Hz, 720p (1280×720)/60Hz, UXGA (1600×1200)/60Hz, 1280×1024/60Hz
	VGA output		1080p (1920×1080)/60Hz, 720p (1280×720)/60Hz, UXGA (1600×1200)/60Hz, 1280×1024/60Hz
	Audio output		1× RCA (Linear, 1 kΩ)
Decoding	Decoding standard		H.265 / H.264
	Like view / playback resolution		Up to 12 MP for the first 4 Ch. , Up to 8MP for the rest
	Synchronous playback		16 channel
HDD	SATA		16 SATA interfaces for 16 HDDs
	Capacity		Up to 8TB capacity for each HDD
External interface	Network		2×10/100/1000Mbps self-adaptive RJ45 interface
	USB		Front panel: 1×USB2.0, Rear panel: 1×USB3.0
	Alarm		16 in / 4 out
	RS-485		2×RS-485 interfaces
General	Power supply		220V/250W (100 to 240 VAC, 47 to 63 Hz, 3A)
	Operating condition		Temperature: -10°C – 55°C (14°F – 131°F) Humidity: 10 - 90%
	Dimensions (W×D×H)		440×323×89mm