


**GE-NVR7208P**

### Features:

- Up to 8 8MP IP camera can be accessed
- 2 HDDs supported, Up to 8TB for each
- ONVIF camera
- Video out: 1 VGA (Max. 1920 x 1080) / 1 HDMI (Max. 3840 x 2160)
- Support: 1 USB 2.0 interface, 1 USB 3.0 interface
- 8 full channel realtime playback
- Perform 5 functions simultaneously: live view, recording, viewing over the network, data backup and playback viewing
- Multiple recording modes: continuous recording, scheduled recording, recording when motion or alarm
- Free Domain (free DDNS): multi-super.ddns.com, declared directly on the recorder
- Support the privacy masking function and motion detection
- Network: RJ45: 10/100/1000M, NTP, PPPoE, UPNP, FPT, Alarm Server, CGI, RTSP, RTMP
- Professional CMS: Unlimited registration recorder, 100 cameras simultaneously display.
- Support remote viewing by phone: Realview, Realview Pro
- Integrated Projects (up to 6 kV)

### Specifications

Model		GE-NVR7208P	
Video / Audio input	IP video input		8 channel
			Up to 12 MP for the first 2 Ch. , Up to 8MP for the rest
	File IP audio input		8 channel
	Two-way audio		1× RCA (2.0 Vp-p, 1 kΩ)
Network	Incoming	Standard	ONVIF, RTSP, HB-protocol
		Bandwidth	160Mbps
	Outgoing	Standard	CGI, RTSP, RTMP(Only for H.264)
		Bandwidth	160Mbps
Video / Audio output	Recording resolution		Up to 8MP for each channel
	HDMI output		4K (3840×2160)/60Hz, 1080p (1920×1080)/60Hz, 720p (1280×720)/60Hz, UXGA (1600×1200)/60Hz, 1280×1024/60Hz
	VGA output		1080p (1920×1080)/60Hz, 720p (1280×720)/60Hz, UXGA (1600×1200)/60Hz, 1280×1024/60Hz
	Audio output		1× RCA (Linear, 1 kΩ)
Decoding	Decoding standard		H.265 / H.264
	Like view / playback resolution		Up to 12 MP for the first 4 Ch. , Up to 8MP for the rest
	Synchronous playback		All channel real-time synchronous playback
HDD	SATA		2 SATA interfaces for 2 HDDs
	Capacity		Up to 8TB capacity for each HDD
External interface	Network		1x 10/100/1000Mbps self-adaptive RJ45 interface
	USB		Front panel: 1× USB2.0, Rear panel: 1× USB3.0
	Alarm		4 in / 1 out
	RS-485		N/A
	E-SATA		N/A
POE	Interface		N/A
	Max. power		N/A
	Standard		N/A
General	Power supply		12V 40W
	Operating condition		Temperature: -10°C – 55°C (14°F – 131°F) Humidity: 10 - 90%
	Dimensions (W×D×H)		340×218×77mm