



■■■ BERNAT® SOFTEE BABY
CAR SEAT BLANKET

MEASUREMENTS

34 x 30 ins [86.5 x 76 cm].

MATERIALS

Bernat® Softee Baby

(Solids: 140 g / 5 oz)

MC: 3 balls (30201 Aqua)

A: 1 ball (02000 White)

Size 5 mm (U.S. H or 8) crochet hook **or size needed to obtain gauge.**

GAUGE

15 sts and 10 rows = 4 ins [10 cm] in pat.

ABBREVIATIONS

www.bernat.com/glossary

INSTRUCTIONS

Note: Ch 2 for turning ch does not count as st.

Main Section

**With MC, ch 129.

1st row: (RS). 1 hdc in 3rd ch from hook. 1 hdc in each ch across. 127 sts. Turn.

2nd row: Ch 2. 1 hdc in back loop of 1st hdc. *1 hdc in front loop of next hdc. 1 hdc in back loop of next hdc. Rep from * to end of row. Turn.**

Rep 2nd row for pat until work from beg measures 23 ins [58.5 cm], ending with a WS row.

*****Divide for legs and shape sides: Next row:** Ch 2. Yoh and draw up a loop in next st. Draw up a loop in next st. Yoh and draw through all 4 loops on hook – hdc2tog made. Hdc2tog over next 2 sts. Pat across next 59 sts. **Turn.** Leave rem sts unworked.

Next row: Ch 2. Pat to last 4 sts. (Hdc2tog) twice. Turn. **Next row:** Ch 2. (Hdc2tog) twice. Pat to end of row. Turn.

Rep last 2 rows 8 times more. 25 sts rem. Fasten off. With RS facing, miss center st. Join yarn with sl st to next st. Pat to last 4 sts. (Hdc2tog) twice. Turn.

Next row: Ch 2. (Hdc2tog) twice. Pat to end of row. Turn.

Next row: Ch 2. Pat to last 4 sts. (Hdc2tog) twice. Turn. Rep last 2 rows 8 times more. 25 sts rem. Fasten off.***

Body Section

Work from ** to ** as for Main Section.

Rep 2nd row for pat until work from beg measures 7 ins [18 cm], ending with a WS row.

Work from *** to *** as for Main Section.

Top edging: 1st row: (RS). Join A with sl st at top right corner of foundation row. Ch 1. Work 127 sc evenly across. **Do not** turn.

2nd row: Ch 1. Working from **left** to right, instead of from **right** to left as usual, work 1 reverse sc in each sc across. Fasten off.

FINISHING

Place WS of Body Section against RS of Main Section aligning leg and side shaping. Pin edges tog.

Edging: 1st rnd: (RS). Join MC with sl st at top left corner of Body Section. Work 1 rnd of sc evenly around outer edges (working through both thicknesses to join Main and Body Sections), working 3 sc in outer corners and sc3tog at inner corner of leg division. Join A with sl st to first sc. Break MC.

2nd rnd: With A, ch 1. Work 1 sc in each sc around, working 3 sc in each corner sc and sc3tog at inner leg division. Join with sl st to first sc.

3rd rnd: Ch 1. Working from **left** to right, instead of from **right** to left as usual, work 1 reverse sc in each sc around. Join with sl st to first sc. Fasten off.

Place vertical markers 7 ins [18 cm] on either side of leg division down length of Body Section. With MC sew through all thicknesses to create openings for legs.



P.O. Box 40, Listowel ON N4W 3H3
"home style... life style... your style."