

PREP 16 PIPE BEVELLING 3" to 16"







WWW.TAG-PIPE.COM Copyright © 2017 TAG PIPE EQUIPMENT SPECIALISTS LTD, All rights reserved.



RANGE: 72 to 385mm i/d

 Functions: External Bevelling Internal Bevelling Facing Counter-boring Weld Removal J-Prepping Compound Bevels

- Materials: Any kind of Steel and Exotic Alloy
- Power: Pneumatic (option of Electric 110v or 220v)



FEATURES & ADVANTAGES

The PREP 16 is the first in TAG's new range of a heavy duty mid-large diameter bevelling machines.

Offering ratchet i/d jaw locking, as well as Ratchet bevel feed control for effortless heavy wall preps. Offered with a 3 HP Pneumatic or 1750 watt electric motor any bevel geometry can be performed within the impressive 3 - 16" range.

J-preps, counter boring, and facing can all be performed, simultaneously, using the correct tooling fitted in (up to) 4 heavy duty hardened multi-position tool holders. Due to its light weight, yet unrivalled power, the PREP 16 is ideal for on-site, off shore, nuclear, and other applications were precision welds are required at an incredible value.

The PREP 16, and its bigger brothers, the PREP 20, the PREP 24, all utilise ratchet feed and locking. This allows effortless set-up, and enables the operator to deliver consistent feed with minimal effort.



SO 9001

Copyright © 2017 TAG PIPE EQUIPMENT SPECIALISTS LTD, All rights reserved.

Tel: +44 (0)1869 324 144 E-mail: sales@tag-pipe.com









The PREP 16 has unrivalled power and stability, utilising a ratchet system for both jaw locking, and bevel feed.



The PREP 16 can also be supplied as an electric version, with a 1750 watt heavy duty, in-line or right angle motor drive, or a heavy duty 3.0 Hp Pneumatic motor.






Tel: +44 (0)1869 324 144 E-mail: sales@tag-pipe.com

PREP 16 TECHNICAL FEATURES:

DESCRIPTION	MEASUREMENT	PNEUMATIC	ELECTRIC
Part Number	-	TP16P	TP16E
Locking tube range	mm / inch (i/d.)	72 - 385mm / 2.8 - 15.1"	72 - 385mm / 2.8 - 15.1"
Recommended working range	mm / inch (o/d.)	72 - 406mm / 2.8 - 16"	72 - 406mm / 2.8 - 16"
Idle speed	rpm	11 - 21	2 - 21
Torque	nm	1770+	1770+
Length of axial feed	mm / inch	50mm / 2"	50mm / 2"
Max operating temperature	C°	55	35
Max acoustic radiation	dB	75	75
Pneumatic motor power	hp	3.0	-
Air consumption	cfm	70	-
Air working pressure	psi	90	-
Air hose connection	inches	3⁄4"	-
Electric motor power	watt	-	1750
Voltage	volt	-	110 / 220
Frequency	Hz	-	50 / 60
Unit weight	kg / lbs	40 / 88	40 / 88
Packing dimensions	mm	760 x 500 x 560mm	760 x 500 x 560mm
Packing weight	kg / lbs	75 / 165	75 / 165

- Electric 110/220v motors only 3 month warranty period.
- All units are supplied complete with all gripping segments to cover the full range of the machine. Service tools, drawings, instruction manual and warranty certificate are also supplied as standard.
- Each machine is supplied with a protective custom built wooden create. •
- We strongly recommend the use of a portable filter lubricator with all our pneumatic models. •





All shapes, sizes and angles available





Tel: +44 (0)1869 324 144 E-mail: sales@tag-pipe.com

90° Facing



PIPE EQUIPMENT SPECIALISTS LTD PRODUCTS INCLUDE:





USA Branch TAG PIPE EQUIPMENT SPECIALISTS INC 527 Michigan Street, South Houston Houston, Texas 77587, USA Tel: +1 713 660 1427 E-mail: sales-usa@tag-pipe.com



TAG PIPE EQUIPMENT SPECIALISTS BVBA Mosten 13, 9160 Lokeren Belgium Tel: +32 486 46 62 93 E-mail: sales-europe@tag-pipe.com

Middle East Branch TAG PIPE EQUIPMENT SPECIALISTS FZE Al Ittihad Street, P.O. Box 3763 Dubai, United Arab Emirates Tel: +971 (0)50 680 3107 E-mail: sales-me@tag-pipe.com ()

India Branch TAG PIPE EQUIPMENT SPECIALISTS PVT Plot No. PAP 3, D 3 Block, Chinchwad, Pune 411 019 Tel: +91 20 6573 4333 E-mail: sales-india@tag-pipe.com



Asia Branch TAG PIPE EQUIPMENT SPECIALISTS PTE Yinhe Bridge West, Beichen District Tianjin, China Tel: +86 139 2001 5417 E-mail: sales-asia@tag-pipe.com

Our company policy is one of continuous improvement. Products may change or vary from those illustrated. Copyright © 2017 TAG PIPE EQUIPMENT SPECIALISTS LTD, All rights reserved.