

• Hardware

Comm. Controller	16C550C compatible
Bus	PCI Express x1
Connector	VHDCI 68

• Serial Interface

Number of Ports	16
Serial Standards	RS-232/422/485
Max. No. of Boards per PC	8

• Serial Line Protection

Surge Protection	4 kV
------------------	------

• Performance

Baudrate	50 bps to 921.6 kbps (supports nonstandard baudrates)
----------	---

• Serial Communication Parameters

Data Bits	5, 6, 7, 8
Stop Bits	1, 1.5, 2
Parity	None, Even, Odd, Space, Mark
Flow Control	RTS/CTS, XON/XOFF, RTS Toggle (RS-232 only)

• Serial Signals

RS-232	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
RS-422	TxD+(B), TxD-(A), RxD+(B), RxD-(A), GND
RS-485-4w	TxD+(B), TxD-(A), RxD+(B), RxD-(A), GND
RS-485-2w	Data+(B), Data-(A), GND

• Physical Characteristics

Dimensions	107 x 161 mm (4.21 x 6.34 in)
------------	-------------------------------

• Driver Support

Windows	Windows 2000/XP/2003/Vista/2008/7/8/8.1/10 (x86/x64), Windows Server 2008 R2/2012/2012 R2/2016 (x64), DOS
---------	---