

POWERPACK SES SERIES

1-2-3 kVA

1:1

PHASE

ONLINE UPS



HOME/OFFICE



EMERGENCY



MEDICAL



INDUSTRY



UPS ONLINE



TOWER



POWER FACTOR



PLUG & PLAY

FEATURES


- High Frequency and True Double-Conversion
- DSP (Digital Signal Processors) Technology
- Input Power Factor Correction (PFC)
- Wide Input Voltage Range (110~300V)
- Output Power Factor 0.9
- Cold Start
- Auto Sensing Frequency
- ECO Mode Operation for Energy Saving
- Selectable Output Voltage via LCD
- Output Bypass Settable via LCD
- Power-On Self Test
- Advanced Battery Management (ABM)
- Short Circuit and Overload Protection
- Automatic Charging in Off Mode
- Auto Control Fan Speed when Loads Varies
- Standard RS232 Communication Port and RJ45 Protection
- USB/SNMP Communication Port (Optional)
- Emergency Power Off (EPO) (Optional)
- Extension Battery Bank (Optional)
- Built-In Isolation Transformer (Optional)

CERTIFICATES




DETAILS

1. AC Input
2. DC Input
3. Outlet
4. Breaker
5. Fan
6. Modem/Tel/Fax
7. RS232
8. USB (Optional)
9. EPO (Optional)
10. SNMP/AS400 (Optional)



Rear Panel
1kVA



Rear Panel
2-3kVA

MODEL										
Capacity	1kVA / 900W			2kVA / 1800W				3kVA / 2700W		
INPUT										
Related Voltage	208V / 220V / 230V / 240 VAC									
Voltage Range	110 ~ 176 VAC (Linear Derating Between 50% and 100% load); 176 ~ 280 VAC (No Derating); 280 ~ 300 VAC (Derating 50%)									
Frequency	40 ~ 70 Hz (Auto Sensing)									
Power Factor	≥ 0.99									
Bypass Voltage Range	-25% ~ +15% (Settable)									
OUTPUT										
Voltage Range	208V / 220V / 230V / 240 VAC (Settable via LCD)									
Voltage Regulation	±1%									
Frequency	45 ~ 55 Hz or 55 ~ 65 Hz (Synchronized Range); 50 / 60 Hz ±0.1 Hz (Battery Mode)									
Waveform	Sinusoidal									
Crest Factor	3:1									
Harmonic Distortion	≤2% (Linear Load); ≤5% (Non-Linear Load)									
Nominal Voltage	Mains Mode to Battery Mode: 0ms Inverter Mode to Bypass Mode: 4ms (Typical)									
Overload Capability	105% ~ 125%: Transfer to Bypass in 30s 125% ~ 150%: Transfer to Bypass in 20s >150%: Transfer to Bypass in 150ms									
EFFICIENCY										
Mains Mode	≥90%			≥91%				≥92%		
ECO Mode	≥95%			≥96%				≥97%		
BATTERIES										
DC Voltage	24 V	36 V	36 V	48 V	72 V	72 V	72 V	96 V	96 V	
Inbuilt Battery	2 x 7Ah	3 x 7Ah	External	4 x 7Ah	6 x 7Ah	External	6 x 7Ah	8 x 7Ah	External	
Charging Current (Max.)	1A		6A	1A		6A	1A		6A	
Recharge Time	8 hour									
ALARMS										
Utility Failure	Beep / 4sec									
Low Battery	Beep / 1sec									
Overload	Beep Twice / 1sec									
UPS Fault	Long Beep									
COMMUNICATIONS										
RS232 (Standard) / USB (Optional)	Supports Windows® 98/2000/2003/XP/Vista/2008/Windows® 7/8/10									
SNMP (Optional)	Power Management from SNMP Manager and Web Browser									
OTHERS										
Operating Temperature	0 ~ 40°C									
Relative Humidity	0 ~ 90% (Non-Condensing)									
Noise Level	≤45 dB (1m)									
DIMENSIONS & WEIGHT										
Dimension WxDxH (mm)	144 x 336 x 214	144 x 414 x 214	144 x 336 x 214	191 x 418 x 335				191 x 464 x 335	191 x 418 x 335	
Packaging Dimension WxDxH (mm)	232 x 417 x 318	231 x 492 x 316	232 x 417 x 318	318 x 533 x 471				320 x 573 x 471	318 x 533 x 471	
Net Weight (kg)	9.5	13	6	18	25.7	10.5	27.2	32	11	
Gross Weight (kg)	10.5	14.2	7	19.5	27.4	12	29	34	12.5	

Makelsan reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Makelsan products previously or subsequently sold. Makelsan does not guarantee the items of the accuracy and completeness.