


JSD Series



Parameter Table

Model	50Hz			60Hz			Pressure		Plunger Dia. (mm)	Stroke Length (mm)	Power KW(HP)	Inlet&Outlet Size	Connection Size
	Flow (lph)	Flow (gph)	SPM	Flow (gph)	Flow (lph)	SPM	(Bar)	(Psi)					
JSD 23/50	23	6.1	100	7.3	28	120	500	7250	12	40	3(4)	DN10	DN10 WN
JSD 40/40	40	11		13	48		400	5800	16				
JSD 63/28	63	17		20	76		280	4060	20				
JSD 105/18	105	28		33	126		180	2610	25			DN15	DN15 WN
JSD 175/11	175	46		55	210		110	1595	32				
JSD 240/8.0	240	63		76	288		80	1160	38				
JSD 300/6.3	300	79		95	360		63	914	42			DN20	DN20 RF
JSD 360/5.5	360	95		114	432		55	798	45				
JSD 450/4.5	450	119		143	540		45	653	50				
JSD 540/3.8	540	143		171	648		38	551	55			DN25	DN25 RF
JSD 650/3.2	650	172	206	780	32	464	60						
JSD 760/2.6	760	201	241	912	26	377	65						
JSD 900/2.3	900	238	285	1080	23	334	70	DN32	DN32 RF				
JSD 1050/2.0	1050	277	333	1260	20	290	75						
JSD 1200/1.8	1200	317	380	1440	18	261	80						
JSD 1350/1.6	1350	357	428	1620	16	232	85	DN40	DN40 RF				
JSD 1500/1.4	1500	396	476	1800	14	203	90						
JSD 1680/1.2	1680	444	533	2016	12	174	95						
JSD 1850/1.0	1850	489	587	2220	10	145	100	DN32	DN32 RF				
JSD 2050/0.8	2050	542	650	2460	8	116	105						
JSD 2500/1.0	2500	661	793	3000	10	145	95						
JSD 3000/0.6	3000	793	951	3600	6	87	105	150	180	DN40	DN40 RF		



Unit: mm

Model	A	B	C	D	Model	A	B	C	D
JSD 23-240	360	98	276.5	724.5	JSD 1500-1680	407	128	275.5	749
JSD 300-360	360	98	266.5	714.5	JSD 1850	417	138	275.5	749
JSD 450-760	328	98	276.5	729.5	JSD 2050	216	148	308	806
JSD 900-1050	349	108	269.5	730.5	JSD 2500	407	128	275.5	749
JSD 1200-1350	359	118	269.5	730.5	JSD 3000	216	148	308	806