

# SS-Type (big capa.)

## Big Capacity!

Big Capacity  
with correct discharge  
in big process line



## Features

Excellent durability by worm gear operation type and suitable for big capacity.  
Very convenient with various kinds of voltages of 220V, 380V, 440V  
Keeping safe using against big capacity by design with needle bearing  
No modification by long time operation because all of each liquid-end parts  
are precisely manufactured with suitable materials according to chemical compatibility.

## Specifications

Test Conditions: water/25°C

		SS-14	SS-24	SS-34	SS-54
Max. Discharge Capacity (L/Min)	50Hz	11.6	20	26.6	45
	60Hz	14	24	32	54
Max. Discharge Pressure (kgf/cm <sup>2</sup> G)		7	3(7)	5	3
Connection (Flange)		KS10K40A			KS10K50A
Motor	Spm(50/60)Hz	48/57	95/114		
	Standard	AC220,380V / 3ø / 60Hz / 0.75Kw		AC220,380V / 3ø / 60Hz / 1.5Kw	
	Option	AC220V,380V/3ø/50 or 60Hz/1.5Kw AC440V/3ø/50 or 60Hz/1.5Kw		AC220V,380V/3ø/50Hz AC440V/3ø/50Hz eG3, d2G4	
Approx. Weight (Kgs)		87	89	92	100