PMZX 系列混合泵 PMZX series mixing pump



乳化、均质、细化、混合、 可调节、多任务、粉液混合的解决方案 Solution for emulsifying, homogenizing, refining, mixing, adjusting, multi-tasking, powder and liquid mixing.



PM系列是一款多功能料液混合泵,它具有混合、剪切、乳化、 均质、分聚、细化、破碎、物料质量改善等功能。该泵相比较传 统生产工艺更加简单方便和经济,提高了生产效率、提升被处理

主要应用于: 食品、饮料、乳制品、添加剂、个人护理、生物制 药、增稠剂、工业应用等。

The PM series mixing pump is for mixing material and liquid with multi-functions, such as mixing, shearing, emulsifying, homogenizing, dispersing, refining, crushing and material improvement. Compared with the traditional production process, the pump is more simple, convenient and economical, which improves the production efficiency and the quality of treated

Mainly used in: food, beverage, dairy products, additives, personal care, biopharma, thickeners, industrial applications, etc.



A=液环式自吸泵 Liquid ring type self-priming pump B=均质混合泵 Homogeneous mixing pump

技术参数 Technical Specifications

粉体最大处理量 Max capacity of powder	9000kg/h					
增稠剂类最大处理 Max capacity of thickeners	3000kg/h(取决于物料粘度和浓度Depends on the viscosity and concentration of the material)					
最高温度 Max temperature	130°C					
材质 Material	304 /316L,1.4301/1.4404,ASME BPE 316L ,1.4435 BN2 Fe≤0.5%					
表面处理 Surface treatment	≤ Ra0.8μm, ≤ Ra0.6μm, ≤ Ra0.4μm					
机射 Mechanical seal	单机封和双机封 Single and double mechanical seals					
机封组合 Mechanical seal combination	详见配置表See configuration table					
进/出口连接 Inlet/Outlet connection	螺纹、卡箍、法兰、无菌法兰 Thread, Clamp, Flange, Aseptic flange					
ìÀiE Certification	3-A-02-11(N.O.1579); MD/06/42-EC (N.O.70521616101-00); FDA 177.2600; USP CLASS-II; EG/VO1935/2004;					

PMZX 系列混合泵 PMZX series mixing pump


DJ-CIP 系列自吸泵 DJ-CIP series self priming pump



CIP系列液环式自吸泵具有超强的自吸能力负压达(0.8bar),将配料罐中的粉体和液体吸入腔室中预处理,并输送至乳化均质泵。

CIP Series liquid ring type self-priming pump has super strong self-priming ability, and negative pressure can reach 0.8bar,the powder and liquid are sucked into the chamber from the dosing tank for pretreatment, and then they're transported to emulsification homogenization pump.






DJ-JZ1 乳化均质泵 DJ-JZ1 Emulsification homogenization pump

JZ1系列泵可对各种复杂的成分如稳定剂、增稠剂、胶体、香精、糖和其他各种添加剂等物料进行,乳化、均质、细化、分散、破碎、混合等功能。其强大的混合能力使物料达到高度的一致性,且提高物料质量。

JZ1 Series pumps can be used for emulsifying, homogenizing, refining, dispersing, crushing and mixing of various complex components such as stabilizers, thickeners, gels, flavors, sugars and other additives. And the strong mixing ability makes the materials reach high consistency and improves the quality of materials,





典型应用行业

Typical applications



食品饮料 Food & beverage

果汁、果酱、冰淇淋、乳制品、食品添加剂、茶饮 料、巧克力、豆奶、香精、沙拉酱、辣椒酱、蛋黄 酱、番茄酱、芥末、酸奶、酸奶油、风味奶、布丁等 工种物料。

Juice, jam, ice cream, dairy products, food additives, tea dirinks, chocolate, soymik, essence, salad dressing, chil sauce, mayonnaise, tomato sauce, mayatard, yogur, sour cream, flavored milk, pudding and other types of material



添加剂和增稠剂 Additives and thickeners

阿斯巴甜、非脱脂奶粉、盐、柠檬酸、糖、鸡蛋粉、 乳清蛋白浓缩物、碳酸钙、蜂蜜、粉末香精等添加 剂, 胶体、果胶、合成增稠剂、淀粉、明胶等各种增 稠剂。

Aspartame, non-skimmed milk powder, salt, citric acid, sugar, egg powder, whey protein concentrate, calcium carbonate, honey, powder essence and other additives, gels, pectin, synthetic thickeners, starch, gelatin and other thickeners.



涂料和油墨 Coating & ink

印刷油墨、油漆、乳胶漆、涂料、纳米涂料、光固化 涂料、涂料阻剂、炭黑分散、釉、膨润土、染料化合 55x3E

Printing ink, oil paint, emulsion paint, coating, nanopaint, photocureable coating, coating abhesive carbon black dispersion, glaze, bentonite, dye compounds etc.



日用化工 Daily chemical

液体洗涤剂、洗手液、洗面乳、硅油乳化、日用香 精、护肤品、化妆品、乳霜、洗发水、沐浴露等。

Liquid detergent, liquid soap, facial cleans emulsified silicone oil, fragrance compound, skin care product, cosmetics,cream, shampoo, shower



石油化工 Petrochemical industry

润滑剂、重油乳化、柴油乳化、改性沥青、催化剂、 蜡乳剂等各种工业石油化工所需均质和乳化的介质。

Lubricant, heavy oil emulsification, diesel oil emulsification, modified asphalt, catalyzer, wax emulsion etc. Which media need to be emulsified and homogenized.



农药 Pesticide

杀虫挤、除草剂、农药乳油、肥料、农药助剂等各种 农药所需乳化均质混合的介质。

Insecticide, herbicide, pesticide missible oil, fertilizer, inert ingredient etc which media need to be emulsified and homogenized.



生物制药 Bio-pharmaceutical

注射剂、抗生素、药乳液、药乳膏、保健品、微胶囊 乳化、洗剂、细胞组织破碎等各种。

emulsifiable paste, health care products, microcapsule emulsification, lotion, cell tissue smash



精细化工 Fine chemical engineering

颜料、染料、塑料助剂、纺织助剂、胶黏剂、树脂乳 化、热熔胶、密封剂、胶水、浆料、整理剂、表面活 性剂、均染剂、炭黑分散、防粘剂、织物整理剂、光 亮剂、皮革助剂、颜料膏等各种化工类所需的乳化和 均质及混合物料等。

Pigment, dyestuff, plastic additive, textile assistant, adhesive, Prightent, dyesturi, passic additive, textue assistant, acclessing resin emulsification, hot melt adhesive, sealant, glue, sizing agent, finishing agent, surfactant, dye leveller, carbon black dispersion, anti-sticking agent, textile finishing agent, brightener, leather auxiliaries, prigment paste etc. Which media need to be emulsified and homogenized.



半导体 Semiconductor


纳米材质分散、解聚等。

Dispersion & depolymerization of nanometer materials etc


PMZX 系列混合泵 PMZX series mixing pump



简单、灵活、 经济、高效 Simple, flexible, economical, efficient



粉体和液体被强力吸入泵腔 Powder and liquid are strongly sucked into the pump chamber



物料被均质混合中 The material is being homogeneously mixed



均质混合物被输送到罐设备中
The homogeneous mixture is transported
to the tank equipment

非常简单清晰的管路布局

- ●多任务的处理;
- ●配置粉体和液体比例可调节;
- 粉体进口设计有阀门,可通过阀门控制粉体被吸入的量,阀门可选择手动或气动;
- ●液体进口设计有阀门,可通过阀门控制液体被吸入的流量;
- ●料斗侧面设计有震动器, 防止粉体堆积结块;
- ●料斗上可配置音叉传感器,自动工作时防止粉体溢出料斗和粉体量过低导致混合物比例不相符。

Very Simple And Clear Piping Layout

- Multiple tasks can be handled simultaneously.
- Ratio between liquid and powder is adjustable.
- The powder inlet is designed with a valve that controls the amount of powder inhaled. The valve can be manual and pneumatic.
- The liquid inlet is designed with a valve that controls the flow of liquid inhaled.
- The side of the hopper is designed with a vibrator to prevent the powder from accumulating and agglomerating.
- The hopper can be configured with tuning fork sensor. when work automatically, the sensor can prevent mixture ratio from inconsistent caused by low amounts of powder, and also can prevent the powder from overflowing.




简单、灵活、经济 Simple, flexible, economical





传感器 Sensor

震动器和阀门 Vibrator and valve



清洗液体灌入料斗 Cleaning liquid is poured into the hopper



清洗管路和料斗 Cleaning pipes and hopper



开启最低排放阀,排干清洗液 Open bottom discharge valve to drain the cleaning solution

非常简单清晰的电器控制布局


- ●自吸泵,可通过变频器控制转速达到控制流量目地;
- ●均质泵,可通过变频器控制转速,达到均质和混合的效果,同 时控制流量目地;
- ●控制箱,设计有电机过载保护电器,防止电机被烧毁;
- ●控制箱,外壳设计工作指示灯,可通过灯分辨工作状态。

Very Simple And Clear Electrical Control Layout

- Self priming pump, can control speed by frenquency inverter to achieve the purpose of controlling the flow.
- Homogeneous pump, can control speed by frenquency inverter to achieve the effect of homogenization and mixing, meanwhile control the flow.
- Console, designed with motor overload protection to prevent motor from being burned.
- Console, the shell is designed with work indicator, can distinguish working condition through the light.

PMZX 混合泵型号说明 PMZX mixing pump model description






PMZX 混合泵选型表 PMZX Mixing pump selection table





均质混合泵 Homogeneous mixing pump 型号 Model DJ-PMZX-13 DJ-PMZX-15	自吸泵 Self-priming pump 转速 Rotate speed (1450-MIN)		乳化均质泵 Emulsifying homogenizing pump 转速 Rotate speed (2950–MIN)		粉体处理量(kg/h) Powder processing capacity						
						DK DE 4- 411	增稠剂粉末(例如, 果胶钠酪蛋白酸盐。	进口	出口	加料斗容量	重量
	自吸泵 (型号) Self-priming pump (Model)	功率 Power (KW)	均匀泵 (型号) Homogeneous pump (Model)	功率 Power (KW)	砂糖类 Sugar class	脱脂牛奶 蛋白粉类 Skim milk Protein powder class	取决于等级和效度) Thickener powder (for example, pectin sodium caseinate, depends on grade and concentration)	Inlet	Outlet	Hopper capacity (L)	Weigh (kg)
DJ-PMZX-13	CIPU-10	5.5	JZ1-10	5.5	500	450	100-200	2*-DN50	1.5"-DN40	45	537
DJ-PMZX-15	CIPU-10	5.5	JZ1-15	7.5	1000	900	200-400	2"-DN50	1.5"-DN40	45	560
DJ-PMZX-17	CIPU-10	5.5	JZ1-20	11	1800	1600	300-500	2"-2.5"-DN50-65	2"-DN50	45	611
DJ-PMZX-19	CIPU-20	7.5	JZ1-30	15	3500	3200	600-1200	DN65-3"-DN80	2"-2.5"-DN50-65	65	640
DJ-PMZX-21	CIPU-20	11	JZ1-35	18.5	5000	4500	1200-2000	DN65-3"-DN80	2.5"-DN65	65	732
DJ-PMZX-24	CIPU-30	-11	JZ1-240	22	10000	9000	1500-3000	4'-DN100	DN65-3'-DN80	65	784

PMZX 混合泵数据图 PMZX Series mixing pump data chart



系列 Model	外形安装尺寸 Assembly Dimension									
	C1	C2	СЗ	C4	F	G	H1	H2	L	L1
DJ-PMZX-13	355	278.5	355	485	1050	1750	1050	300	1011	624
DJ-PMZX-15	355	257	355	485	1050	1750	1050	300	1011	624
DJ-PMZX-17	355	283.5	384	514	1050	1750	1050	300	1011	624
DJ-PMZX-19	355	256.5	384	514	1050	1750	1050	300	1011	624
DJ-PMZX-21	355	243	384	514	1050	1750	1050	300	1124	624
DJ-PMZX-24	383	243	404	514	1050	1750	1050	300	1124	624

注意;以上数据图相关尺寸不作为实物最终依据,东正保留对于数据更新权限不再另行通知。 Note: The relevant dimensions of the above data diagrams are not regarded as the final basis of the actual object. DONJOY reserves the right to update the data without further notice.