

## Data Sheet

# 1290 Direct Drive Process Pressure Gauge

### FEATURES

- Accuracy complies with  $\pm 0.5\%$  (ASME B40.1, Grade A)
- Gearless design
- Ideal for shock and vibration applications
- External dial adjustment

### TYPICAL USES

- Refineries
- Offshore / Power - Power Plants



**1290**  
4 1/2" dial size



### SPECIFICATIONS

Accuracy:  $\pm 0.5\%$  of span (ASME B40.100, Grade 2A)  
 Size: 4 1/2"  
 Range: 15 to 2,000 psi

Process Connection Location: Lower

Process Connection Size: 1/4 NPT Male, 1/2 NPT Male

Case Style: Solid front with pressure relief back

Movement: Adjustable

Movement Materials: 300 SS

Window Material: Acrylic

Dial: Aluminum, white background, black scale

Pointer: Aluminum

Weather Protection: Dry Case: IP54

Mounting: Stem or Surface

Approvals: CRN

### WETTED COMPONENTS

Bourdon Tube	Process Connection	Joints
Inconel® 750X, 304 SS capillary	316L SS	Welded

### NON-WETTED COMPONENTS

Case	Ring	Back Cover
ABS Thermoplastic	302 SS	Polypropylene

### KEY BENEFITS

- Low volumetric displacement - compatible with mini diaphragm seal
- Selection of Measurement Units (psig and dual scale, kg/cm<sup>2</sup>/psi)
- Optional NIST Traceable Calibration Chart

### MIN/MAX TEMPERATURE LIMITS (1259 ONLY)

Version	Ambient	Process	Storage
Dry	-20°F to 200°F (-29°C to 93°C)	-20°F to 250°F (-29°C to 121°C)	-40°F to 250°F (-40°C to 121°C)
Glycerin Fill	20°F to 150°F (7°C to 66°C)	20°F to 200°F (7°C to 66°C)	0°F to 150°F (-18°C to 66°C)
Silicone Fill	-40°F to 150°F (-40°C to 66°C)	-40°F to 200°F (-40°C to 93°C)	-40°F to 150°F (-40°C to 66°C)

# Data Sheet

## 1290 Direct Drive Process Pressure Gauge

ORDERING CODE	Example:	451290	W	D	02	L	XC4	15#
<b>Dial Size/Model Code</b>								
451290 - 4½" ABS thermoplastic case, solid front. Direct drive		451290						
<b>System (tube and process connection)</b>								
W - Inconel <sup>®</sup> direct drive coil X750, SS process connection			W					
<b>Case Design</b>								
D - Dry (IP54)				D				
<b>Process Connection Sizes</b>								
02 - ¼ NPT Male						02		
04 - ½ NPT Male								
<b>Process Connection Location</b>								
L - Lower						L		
<b>Options (If choosing an option(s) must include an "X")</b>								X_
C4 - Individual calibration chart in accordance with ASME B40.100:2013. Accuracy traceable to N.I.S.T								C4
6B - Cleaned for gasses, oxygen service								
NH - SS tag wired to case								
RG - Regular glass								
<b>Range (coding examples only, see range table on page 3 for all standard ranges)</b>								
<b>Single Scales</b>								
15# - 15 psi								15#
1BR - 1 bar								
1KG - 1 kg/cm <sup>2</sup>								
100KP - 100 kilopascal								
<b>Dual Scales</b>								
2KSC/# - 2 bar inner scale, 30 psi outer scale								

# Data Sheet

## 1290 Direct Drive Process Pressure Gauge

Single Scale	Dual Scale	
	psi	KSC - inner
15#	2	0/30
30#	7	0/100
60#	11	0/160
100#	14	0/200
150#	21	0/300
160#	28	0/400
200#	35	0/500
300#	42	0/600
400#	70	0/1000
500#	105	0/1500
600#	120	0/2000
800#		
1000#		
1500#		
2000#		

### DIMENSIONS

For reference only, consult Ashcroft for specific dimensional drawings

