

Small Pressure Gauges- Brass Internals



MODEL : SPGB (Dry Case)

LFSPGB (Liquid Filled Case)

Features

- Designed to fulfill most industrial as well as commercial applications
 - Range : (-)1 to 250 kg/cm²
 - Bourdon in Ph Bronze / Brass
 - Accuracy ±2% FSD
 - Unit of measurement - kg/cm², bar, psi
-
- Small dial Pressure Gauges are developed for OEM applications in compressed gases, Lubricating circuits, air filter Regulators, Gas cylinders etc.



Specifications

Dial	40mm / 50mm / 63mm in Aluminium, white background, black markings
Case	Pressed steel, epoxy painted black / SS304
Protection	IP-68 for 50mm & 63mm, SS Case only (Not Applicable for 40mm SS Case & all Pressed Steel Cases)
Bourdon	Ph Bronze / Brass
Socket	Brass
Movement	Brass
Range	Rrefer table
Accuracy	±2% FSD
Blow out disc	Provided (on top) for 50mm & 63mm dials Not Applicable for 40mm Dial
Temperature suitability	Ambient (-)20°C to 60°C, Media 60°C
Temperature Effect	Within ±0.4% FSD/10°C, when temperature changes from reference temperature of 20°C (as per EN-837 standard)
Optional	Glycerine filled case (in SS case of 50mm & 63mm only) Built in snubber CE

Note: For availability ranges in different dial sizes, please refer table



Range vs Dial Size

Range bar(g), kg/cm2(g)	Dial Size		
	1-1/2" Dial	2" Dial	2-1/2" Dial
(-)1 to 0 Vacuum	x	Yes	Yes
(-) 1 to (+)1.5	x	Yes	Yes
(-) 1 to (+)3	x	Yes	Yes
(-) 1 to (+)5	x	Yes	Yes
(-) 1 to (+)9	x	Yes	Yes
(-) 1 to (+)15	x	Yes	Yes
(-) 1 to (+)24	x	Yes	Yes
(-) 1 to (+)39	x	Yes	Yes
0 to 1	x	Yes	Yes
0 to 1.6	x	Yes	Yes
0 to 2	Yes	Yes	Yes
0 to 2.5	Yes	Yes	Yes
0 to 4	Yes	Yes	Yes
0 to 6	Yes	Yes	Yes
0 to 10	Yes	Yes	Yes
0 to 16	Yes	Yes	Yes
0 to 25	Yes	Yes	Yes
0 to 40	x	Yes	Yes
0 to 60	x	Yes	Yes
0 to 100	x	Yes	Yes
0 to 160	x	Yes	Yes
0 to 250	x	Yes	Yes


Yes = Range Available X = Range not available

The parameters mentioned here are the standard specifications / values generally used for most of the process applications. Any other specification not appearing here also can be provided as per customer requirement.

Under Technical Collaboration with M/s. Gauges Bourdon, France

Ordering Information

MODEL



e.g. For 1/4"NPT(M), Code: **T06NTM**

Note: 40mm Dial, Standard Connection 1/8" Male threads only
 50 / 63mm Dial, Standard Connection 1/8" or 1/4" Male threads only
 Any other Connection shall be provided through Adaptors

Sample Model Code: **LFSPGB-P-63-S4S-BRS-BRS-BRS-T06NTM-(0-250)-PSI-GLY**