

Main Specifications

- ▼Size
Standard: 2.5" , 3"
Option: 2" , 4"
- ▼Window
Glass (with raised edge)
With O-ring sealed
- ▼Temperature range
Please refer to temperature range table
Min.: -40°C
Max.: +400°C
- ▼Mount type
Back mount with spring
- ▼Spring size
4.9 x 92.3 mm
(For larger pipe diameter, larger spring size is available upon request)
- ▼Application
Clamp on 1" -2" pipes with spring
- ▼Protection level
IP 54

Other Specifications

- ▼Housing
Stainless steel
- ▼Bezel
Stainless steel
- ▼Back housing
Stainless steel
- ▼Pointer
Aluminum with black enamel
Adjustable pointer
- ▼Dial face
Aluminum with white enamel
All black scale
- ▼Measuring elements
Bi-metal spiral spring
- ▼Temperature accuracy
2%
- ▼Operating temperature
Stabilization: 3/4* full scale
Short-time: 1* full scale

Pipe-Clamp Surface Thermometer
Model: BT-SM



Due to the variety of customization, the picture is only for reference, please confirm the actual item with our sales. (If there is any change on specification, please take the latest version as standard.)

Features

- Original imported from German BITHERMAL brand
- Clamp on pipes surface with a spring instead of intrusive method
- All stainless steel design
- Clamp on 1" -2" pipes with spring to measure surface temperature

How to order

BT-SM 3" -40...400°C 92.3mm PC
| | | | |

Model	Size	Temperature range	Spiral length	Window
BT-SM	2.5"	-40...400°C	92.3mm	PC
	3"	Others (please refer to temperature range table)	Others (please specify)	Glass

Safety glass

Ordering example: BT-SM - 3" - (-40...400°C) - 92.3mm - PC

Temperature range table

Temperature range (for $\varnothing 2.5''$, 3'')
-40+200°C
-40+40°C
-40+120°C
-30+70°C
-30+50°C
-20+40°C
-20+60°C
-20+100°C
-10+60°C
-10+50°C
0~60°C
0~80°C
0~100°C
0~120°C
0~160°C
0~200°C
0~250°C
0~300°C
0~400°C

Other requests:

- Inspection report (issued by Re-Atlantis)
- Third party notarized document
- O-ring material (for sealing window):
rubber (standard), silicone rubber
- Customized dial face (scale, color, etc.)
- Thermometer size: 4"
- Tag
- Back housing material: SS 316
- Peak hold pointer
- Thermometer size: 2"