

Main Specifications	Other Specifications
<p>▼Size 9"</p> <p>▼Window Glass</p> <p>▼Stem Material: Stainless steel Length: 64mm</p> <p>▼Process connection 3/4" PT</p> <p>▼Temperature range Min.: 80°C Max: 135°C</p> <p>▼Temperature error Standard: calibrated temp. Every ±4°C max. error: ±0.25% F.S</p> <p>▼Application Food / Pharmaceutical / Canning industry</p>	<p>▼Top cover Screw Fixed</p> <p>▼Housing Aluminum alloy with black enamel</p> <p>▼Liquid in glass Mercury</p> <p>▼Dial White board with black scale V-shape</p> <p>▼Measuring elements Thermal expansion linearity of mercury</p> <p>▼Accuracy ±0.5°C</p> <p>▼Operating temperature Steady: 3/4* full scale Short time: 1* full scale</p> <p>▼Other requests (Option) Delivery inspection report Tag Third party notarized documents Thermometer casing</p>

Industrial Glass Thermometer (for autoclave type)

Model: FDT

Introduction

FDT thermometer are specially designed for high temperature sterilization equipment in food, pharmaceutical, and canning industry. The thermometer may have an optimum application with remote recording thermometer and pressure gauge.



Due to the variety of customization, the picture is only for reference, please confirm the actual item with our sales. (If there is any change on specification, please take the latest version as standard.)

Features

- OEM Service
- Mercury thermometer with well characteristic of constant thermal expansion.
- Red scale reflector to ensure legibility

How to order

Model	Size	Code	Thread Size	Code	Thread Type	Code	Stem Length	Code	Stem Material	Temperature Range
FDT	9"	1	3/4"	P	PT	64	64mm	SS	Stainless steel	80°C~135°C

Ordering Example: FDT - 9" - 1 - P - 64 - SS - 80°C~135°C