

隔膜阀 Diaphragm valve



不锈钢执行器
Stainless steel actuators

塑料执行器
Plastic actuators

气动隔膜阀 Pneumatic diaphragm valve

- ◆ SIZE: 1"-4", DN25-DN100
 - ◆ 最高温度: -30到150°C(分离2片式膜片 EPDM+PTFE)
 - ◆ 最高温度: -30到130°C
(单层膜片EPDM/双层粘合式膜片EPDM+PTFE)
 - ◆ 最高压力: 单向(DELTA P=100%)
常闭橡胶8bar, PTFE 6bar(选项)
常闭橡胶6bar, PTFE 4.5bar(标准)
常开和双作用橡胶8bar, PTFE 6bar
 - ◆ 换装不同的执行器可以满足更高压力等级
 - ◆ 锻造阀体: 1.4404/316L /1.4435 Nb2 Fe < 0.5%, ASME BPE 316L
 - ◆ 铸造阀体: 1.4404/316L
 - ◆ 连接方式: 焊接、卡箍、法兰、螺纹
-
- ◆ SIZE: 1"-4", DN25-DN100
 - ◆ Max temperature: - 30 to 150 °C (depending on diaphragm)
(stainless steel actuator)
 - ◆ Max temperature: - 30 to 130 °C (depending on diaphragm)
(plastic actuator)
 - ◆ Max pressure: one way (DELTA P = 100%)
Normally close EPDM 8 bar, PTFE 6 bar (option)
Normally close EPDM 6 bar, PTFE 4.5 bar (standard)
and double action EPDM 8 bar, PTFE 6 bar
 - ◆ Assemble different actuators can meet the higher pressure rating
 - ◆ Forging body: 1.4404/316 L /1.4435 Nb2 Fe < 0.5%, ASME BPE 316L
 - ◆ Casting the body: 1.4404/316 L
 - ◆ Connection: welding, clamp, flange, thread



塑料手轮隔膜阀
Plastic handwheel

手动隔膜阀 Mnaual diaphragm valve

- ◆ SIZE: 1"-4", DN25-DN100
 - ◆ 最高温度: -30到150°C(分离2片式膜片 EPDM+PTFE)
 - ◆ 最高温度: -30到130°C
(单层膜片EPDM/双层粘合式膜片EPDM+PTFE)
 - ◆ 最高压力: 10bar
 - ◆ 锻造阀体: 1.4404/316L/ASME BPE 316L/1.4435 BN2 Fe ≤ 0.5
 - ◆ 铸造阀体: 1.4404/316L/ASTM A351 CF3M
 - ◆ 连接方式: 焊接、卡箍、法兰、螺纹
-
- ◆ SIZE: 1 " - 4 " , DN25-DN100
 - ◆ Max temperature: - 30 to 150 °C (depending on diaphragm)
(stainless steel wheel)
 - ◆ Max temperature: - 30 to 130 °C (depending on diaphragm)
(plastic wheel)
 - ◆ Max pressure: 10 bar
 - ◆ Forging body: 1.4404/316L/ASME BPE 316L/1.4435 BN2 Fe ≤ 0.5
 - ◆ Casting the body: 1.4404/316L/ASTM A351 CF3M
 - ◆ Connection: welding, clamp, flange, thread