



IN-LINE SPRING FOOT VALVE



JD Series

SOCKET JD100 / THREAD JD200

Size: 1/2" - 2"

Test Press: 15kgf/cm² (bar) Working Press: 10kgf/cm² (bar)
225psi 150psi

MATERIALS OF CONSTRUCTION

No	Part	Material	PCS
1	UPPER BODY	UPVC	1
2	FILTER	UPVC	1
3	SEAL	EPDM	1
4	SPIGOT	UPVC	1
5	SPRING	SUS 304	1

DIMENSIONS TABLE

Nom	SIZE	15mm	20mm	25mm	32mm	40mm	50mm	
		(1/2")	(3/4")	(1")	(1-1/4")	(1-1/2")	(2")	
d	JIS (mm)	Socket	20	26	32	38	48	60
		Thread	PT1/2	PT3/4	PT1	PT1-1/4	PT1-1/2	PT2
	ANSI (inch)	Socket	0.840	1.050	1.315	1.660	1.900	2.375
		Thread	NPT1/2	NPT3/4	NPT1	NPT1-1/4	NPT1-1/2	NPT2
	DIN (mm)	Socket	20	25	32	40	50	63
		Thread	R1/2	R3/4	R1	R1-1/4	R1-1/2	R2
P	JIS (mm)	22.2	25.4	28.6	31.8	34.9	38.1	
	ANSI (inch)	0.875	1.000	1.125	1.250	1.375	1.500	
	DIN (mm)	16.0	18.5	22.0	26.0	31.0	37.5	
D1		17	21	28	35	40	52	
D2		35	35	45	52	60	73	
D3		37	37	47	54	62	75	
B		56	56	71	102	102	114	
L		129	129	149	173	173	211	

