

RK330-01B Atmospheric Temperature Sensor is a professional measurement of air temperature, relative humidity & barometric pressure. Sensors are built-in the water-proof and anti-UV shelter. It is widely used in agriculture, forestry, meteorology as well as a climate chamber, warehousing and other places. This model also can be equipped with 11 plates radiation shield(RK95-01) to protect the sensors from solar radiation and rain.

### FEATURES

- According for WMO NO:8 I,III(2018)
- Fast response time
- Long service life
- Low consumption
- Good stability of output
- PT100 temperature and high humidity environment for long-term use
- Can integrated temperature humidity air pressure at the same time



### APPLICATIONS


- Environmental monitoring
- Livestock farm
- Storage
- Forestry
- Greenhouse
- Agriculture

### TECHNICAL SPECIFICATION

Item	Technical Specification
	Temperature RTD/PT100
Range	-40°C to +60°C
Resolution	± 0.1°C
Accuracy	±0.3°C
Supply	5VDC, 12-24VDC
Output Signal	4-20mA,0-5V,0-10V,RS485(MODBUS),IIC <sup>Ⓞ</sup>
Current Consumption	<20mA
Operating Temperature	-40°C-+80°C
Ingress Protection	IP65
Storage	10-60°C@20%-90%RH
Weight(unpacked)	120g
Probe material	ABS
Radiation Shield(optional)	RK95-01,11 plates

<sup>Ⓞ</sup>Analog output only is proper for one or two measurement parameters.

## DIMENSION



Unit:mm

## MOUNTING

1. Install the product in stable environment area, avoid direct sunlight, away from windows air-conditioning, heating and other equipment. Otherwise it will cause measurement inaccuracies.
2. Fixing rail is optional.
3. If you use indoor, recommends clamp to install, as shown on the right picture.



## PARAMETER SELECTION TABLE

Remark	Series	Type	Parameter	Output	Accessory	Cable Length	
RK							
	330						
		01					
			A				Temperature & Humidity
			B				Temperature, Humidity, Pressure
			C				Temperature
			D				Humidity
				A			4-20mA
				B			0-5V
				C			0-10V
				D			RS485
				E			IIC
				F			SDI-12

					A		
					B		With clamp
					N		Without any accessory
						3000	Units:mm (typ)
						...	Units:mm

Example: RK330-01AAN3000    Parameter: temperature & humidity    Output: 4-20mA    Without any accessory    Cable Length:3m.

 Complies with applicable CE directives.

Specifications subject to change without notice. Version 3.0

Copyright © 2015 Hunan Rika Electronic Tech Co.,Ltd

**Hunan Rika Electronic Tech Co., Ltd**

Add: Building B5, Taskin, Yuhua District,  
Changsha City, Hunan Province,  
China



+86-731-85132979



info@rikasensor.com



www.rikasensor.com