




HANS™ Pre-Treatment Module

Iron/Arsenic - Softener - Carbon



Space Saving Footprint
Compact design to solve water needs



Modular Flexibility
Provide scalability to meet your volume needs



Easy Installation
Plug & play deployment



Smart Monitoring
Wi-Fi enabled for remote monitoring

Commercial • Industrial • Agriculture • Healthcare • Hospitality • Food & Beverages

HANS™

Premium Water

Iron/Arsenic- Softener-Carbon Technical Specifications

Operating Specification

Water temperature (min/max)	2°C to 35 °C
Ambient temperature (min/max)	2°C to 48°C
Feed pressure (min/max)	30 PSI to 80 PSI
Continuous / Peak Operation	30 LPM @ 15 PSI / 42 LPM @ 25 PSI
Drain Flow Max	30 LPM
Indoor/Outdoor Capable	UV protection on all exterior parts
Weight (Dry, with media)	272 KG
Exterior Dimensions	533 mm x 737 mm x 1359 mm
Power	US: 120 V / 60Hz EU: 220 V / 50Hz dedicated GFCI

Stage 1 - Iron/Arsenic

Media Tank size	254 mm x 1118 mm
Backwashable Filter Cell	254 mm x 1118 mm Tanks in parallel with connecting manifold
Backwashable Filter Size	2.5 cu ft of Katalox Light

Stage 2 - Softener

Media Tank size	254 mm x 1118 mm
Backwashable Filter Cell	254 mm x 1118 mm - Tanks in parallel with connecting manifold
Backwashable Filter Size	2.5 cu ft of 10% Cross Link Resin - up to 80,000 Grain Capacity

Stage 3 - Carbon

Media Tank size	254 mm x 1118 mm
Backwashable Filter Cell	254 mm x 1118 mm - Tanks in parallel with connecting manifold
Backwashable Filter Size	2.5 cu ft of Catalytic Carbon

Electronics

AC Inlet:1 interchangeable	US:120 V/ 60Hz EU:220 V/50Hz
Pressure Sensors:2	1 : Inlet 0 -100 PSI, 2 : Outlet 0 -100 PSI
Flow Sensor:1	1 : Outlet 0 - 189 LPM
Wireless Communication	2 way capable
Firmware Updates	WiFi update capable / USB Port

Software

Encryption	TLS 1.2
Operation	Automatic regen & backwash

For Reduction of:

• Iron	• Chloramine
• Arsenics	• Lead
• Sediment to 5 Microns	• VOCs
• Turbidity	• Odor
• Hardness	• Barium
• Chlorine	• Radium



Iron/ Arsenic Softener Carbon

Follow us on:



Headquarters: 54/18 Bui Quang La, Ward 12, Go Vap District, HCMC, Viet Nam
Office: 12 DHT10B, Dong Hung Thuan Ward, District 12, HCMC, Viet Nam
Phone: (028) 6258 5368 - (028) 6291 9568
Email: info@atswatertechnology.com
Website: www.atswatertechnology.com



Specifications subject to change without notice.
**Input levels outside of device parameters may require pretreatment such as a water softener or iron breaker.
Designed and assembled in an ISO 13485 facility in Michigan.
©2020 HANS Power & Water, LLC 2020911
ML082 Rev A