

BRACKISH WATER REVERSE OSMOSIS SYSTEM


ADES-BRO8 Series

Model
ADES-BRO8-010

GENERAL INFORMATION

With the state of art technology, ATS has always in place decades of expertise to build a robust and reliable Reverse Osmosis system for the challenging markets. Using RO membrane from LG Chem NanoH₂O with Core technology.

Thin-film-Nano-Composite (TFN) instead of conventional technology Thin-Film-Composite (TFC). TFN gives higher performance compared to TFC regards to Flow rate, salt rejection and operating pressure.



*The above photo of ADES-BRO8-010 is for illustration purpose only.

ADES-BRO8-010 system includes:

- ✓ Vertical multistage pump with IE3 motor & VFD.
- ✓ 8" TFN spiral wound RO membrane (LG Chem NanoH₂O).
- ✓ 5µm cartridge pre-filter (ePore).
- ✓ Low pressure piping: uPVC, Sch80 with NSF / ANSI certificate.
- ✓ High pressure piping: SUS316, Sch5.
- ✓ PLC & HMI 7" control panel.
- ✓ SS400 with 3 layers epoxy coated steel skid frame.
- ✓ FRP membrane housing (Codeline – Pentair).
- ✓ Automatic control with electric valves.
- ✓ Permeate, Concentrate & Recirculation flow indicators.
- ✓ Pressure sensors & pressure gauges.
- ✓ ORP, EC meters & controllers.
- ✓ Connection with JIS10K Flange.
- ✓ 380 – 415V / 3Phase / 50Hz power supply.
- ✓ Anti-scalant dosing pre-filled with 1 pail (SpectraGuard 360 – PWT chemical).

Available Options

- Membrane cleaning skid (CIP).
- pH sensors added.
- High rejection membrane elements.
- Feed / Permeate blending.
- DIN / ANSI flange connection.
- SUS304 / SUS316 skid frame.

System Features / Benefits

- Easy to operate, plug and play system.
- Fully automated system.
- Optimized footprint.
- Designed to fit in a high cube container.
- High permeability at low feed pressure.
- Significantly reducing operating costs.

Cartridge Filter

Model	ePore
Maximum Differential Pressure (bar)	3 bar at 25°C
Max temperature	70°C
Filter Element Model	IM05B3
Length (inch)	30
Media Efficiency (µm)	5 (Nominal)
Material	PP

RO Membrane Specifications

Membrane Model	LG BW 400 ES
Effective Membrane Area (m ²)	37
Diameter x Length (inch)	8 x 40
Stabilized Salt Rejection (%)	99.6
Feed Spacer (mil)	34
Filtration Flux (LMH)	Up to 27

Feed water quality¹

SDI	≤ 5
Oil & Grease (mg/L)	≤ 0.1
TOC (mg/L)	≤ 3
COD (mg/L)	≤ 10
Free Chlorine (mg/L)	≤ 0.1
Fe ²⁺ (mg/L)	≤ 4
Fe ³⁺ , Mn, Al (mg/L)	≤ 0.05

¹Please contact us if the feed water source is worse than the above standard.


System and Operating Configuration

Model	ADES-BRO8-010
No. of Membranes	12
No. of Pressure Vessel	3
Dimension ² L x W x H (mm)	6000 x 1300 x 2400
Approx. Weight (kg)	1640
Permeate Flow (m ³ /h)	8 - 10
Recovery (%)	75 (±5)

²The dimensions of the system may vary and subject to change without prior notice.

Mechanical Connections (Flange)²

Feed Port	DN65 (2½")
Off-spec Port	DN40 (1½")
Permeate Port	DN40 (1½")
Concentrate Port	DN25 (1")
Drain Port	DN25 (1")
Pressure Vessel Type	Multi-port™



ATS WATER TECHNOLOGY CO., LTD.

Headquarters: 54/18 Bui Quang La, Ward 12, Go Vap District, HCMC, Viet Nam

Office: 12 DHT10B, Dong Hung Thuan Ward, District 12, HCMC, Viet Nam

[T] (028) 6258 5368 - (028) 6291 9568 [E] info@atswatertechnology.com

[W] www.atswatertechnology.com

