

SpectraGuard™ 101 is a ready for use liquid antiscalant/dispersant that has been proven as a superior pretreatment in RO feed waters. With its ability to handle high levels of carbonate, sulfate and silica scale, as well as low concentrations of iron, SpectraGuard™ 101 ensures stable performance with complete control of the feed water chemistry.

### Features / Benefits

- Phosphate-free formula reduces negative impact on the environment
- Stable molecular structure maintains integrity in high pH, high temperature and high salinity applications
- Classified for use in membrane systems producing drinking water (ANSI/NSF Standard 60)

### Uses

- Control of calcium carbonate, calcium sulfate, barium sulfate, calcium fluoride, silica, and hydroxides of iron and aluminum
- Can be blended with other pretreatment formulations from Professional Water Technologies to reduce chemical dosing equipment

### Specifications

Appearance	Colorless/Amber
pH	2.50 – 3.50
Density (kg/liter)	1.00 – 1.10



### Packaging

Pail: 5 gallon/18.9 liter

Tote: 275 gallon/1,040 liter

Drum: 55 gallon/208 liter

Bulk: available upon request

*For special packaging options, please contact PWT or your local distributor.*

**SpectraGuard™ 101**  
LIQUID REVERSE OSMOSIS ANTISCALANT

# SpectraGuard™ 101

LIQUID REVERSE OSMOSIS ANTISCALANT

## General Mixing & Application Instructions for SpectraGuard™ 101

1. Typical sea water dose rates are 0.5 to 1.0 mg/l, and typical brackish water dose rates are 2.0 to 5.0 mg/l.
2. Contact Professional Water Technologies™ or your local distributor for custom chemical dosing recommendation.
3. We use ProDose to determine your scaling potential and recommended chemical dosing levels.

## ProDose XPRT™ – Scaling Prediction Software

ProDose XPRT™ uses the most accurate scaling prediction calculations available to accurately determine effective antiscalant dosage, and cleaning chemical usage. The user can enter multiple cases to study various operating conditions, directly enter concentrate analysis, and select the best PWT product and dosage for the application.

*ProDose XPRT™ is available upon request only. Please contact your PWT representative for more information.*

The screenshot displays the PWT ProDose software interface. At the top, there is a navigation bar with various parameters: UNITS (US), TEMPERATURE (Fahrenheit, 81.00), PERMEATE FLOW (81.00), RECOVERY (75.0%), ANTISCALANT (SpectraGuard Liquid), DOSAGE (2.95 PPM), SOURCE (Well Water), PROJECT NAME (Project 1), and CASE (1). The main interface is divided into several sections: PROJECT INFORMATION (with icons for Project Information, Water Quality, System Information, Chemical Selection, Calculations, and Report), OVERVIEW (with fields for Client Name: City of San Diego, Project Name: Project 1, Location, Prepared By, Date: 5/1/2016, and Water Type: Well Water), MEASUREMENTS (with preset units: CGS, Metric, U.S.; Temperature: Deg F; Flow Rates: Gal/min; Mass Units: lb; and an Enter button), COMMENTS (OPTIONAL) (with a large text area), and TOTAL CASES (1 AVAILABLE) (with a table showing Case 1, Modified Date 5/27/2016, and a Selected Case Description field).



PWT Headquarters & Manufacturing  
1048 La Mirada Court, Vista, California 92081

Toll-Free: 800.914.9072 | Direct: 760.639.4400 | Fax: 760.639.4439  
Email: sales@pwtchemicals.com | www.pwtchemicals.com



Headquarters: 54/18 Bui Quang La, Ward 12, Go Vap District, HCMC, Viet Nam  
Office: 12 DHT10B, Dong Hung Thuan Ward, District 12, HCMC, Viet Nam  
Phone: (028) 6258 5368 - (028) 6291 9568  
Email: info@atswatertechnology.com  
Website: www.atswatertechnology.com