

# MULTIUSE POLES

## INSULATING POLES



Multiuse pole with only one section made of polyester and fibreglass tube Ø 32 mm and polyurethane foam filling with U (Universal), B (Bayonet) or H (Hexagonal) head.

Includes carrying bag.

According to IEC 60855 and UNE-EN-50508 standards.

### Mod. BSC-M3

- Length: 1.5 meters
- Working voltage: 30 kV
- INDOOR and OUTDOOR use (Humid environment)

Code	Ref.
616700	BSC-M3U
616701	BSC-M3B
616702	BSC-M3H

### Mod. BSC-M4

- Length: 2 meters
- Working voltage: 45 kV
- INDOOR and OUTDOOR use (Humid environment)

Code	Ref.
616703	BSC-M4U
616704	BSC-M4B
616705	BSC-M4H

### Mod. BSC-M5

- Length: 2.5 meters
- Working voltage: 66 kV
- INDOOR and OUTDOOR use (Humid environment)

Code	Ref.
616706	BSC-M5U
616707	BSC-M5B
616708	BSC-M5H

### Mod. BSC-M6

- Length: 3 meters
- Working voltage: 132 kV
- INDOOR and OUTDOOR use (Humid environment)

Code	Ref.
616709	BSC-M6U
616710	BSC-M6B
616711	BSC-M6H

IEC 60855  
UNE-EN-50508