



## Crimping

Mechanical crimping tools

### K 35/4 Crimping tool for interchangeable dies 6 - 150 mm<sup>2</sup>



**K4**  
SERIE

- ▶ Very comfortable: Tool-less crimping die change
- ▶ Optimised for cable glands and control cabinet construction
- ▶ Energy-efficient and low-maintenance mechanical drive

#### Characteristics

- Narrow crimping
- Less effort due to extendible telescopic handle
- Flexible use: Head rotates 360°
- Fast, change of crimping die without readjustment by special fixing system







































#### Technical data

Length Stepless 420-590 mm

Weight 1.9 kg

Item	Part No.	
Crimping tool for interchangeable dies 6 - 150 mm <sup>2</sup>	<b>K354</b>	
Accessories	Part No.	Page
Steel carrying case	SK65L	193

## Available dies for Series 4 for K 35/4

Suitable for	Connection material	Crimping range mm <sup>2</sup>	Crimp profile	Page
<b>Copper tubular cable lugs and connectors</b>				
Tubular cable lugs and connectors blue connection for compacted conductors acc. to DIN EN 60228		6 - 150		314
Tubular cable lugs and connectors, standard type, tubular cable lugs for switchgear connections		6 - 150		314
Insulated cable lugs and compression joints, standard type, insulated pin terminals		10 - 70		314
Tubular cable lugs and connectors for fine stranded conductors		10 - 35		315
Tubular cable lugs and connectors for solid conductors		1.5 - 16		315
<b>Tubular cable lugs and connectors, Ni, VA</b>				
Stainless steel tubular cable lugs and connectors		0.5 - 2.5		315
Stainless steel tubular cable lugs and connectors		4 - 16		315
Nickel tubular cable lugs and connectors		0.5 - 2.5		315
Nickel tubular cable lugs and connectors		4 - 16		315
<b>Copper compression cable lugs and connectors to DIN</b>				
Copper compression cable lugs (DIN 46235) and connectors (DIN 46267, part 1) acc. to DIN		6 - 120		316
<b>Terminals, connectors and pin terminals acc. to DIN, copper</b>				
Solderless terminals (DIN 46234), connectors and pin terminals (DIN 46230) acc. to DIN		6 - 35		316
Insulated solderless terminals and connectors		10 - 16		316
<b>Sleeves for compacted conductors and sector-shaped conductors, copper</b>				
Pre-rounding dies for sector-shaped Al and Cu conductors		10 sm - 150 se / 120 sm		317
<b>Aluminium compression cable lugs and connectors acc. to DIN</b>				
Aluminium compression cable lugs and connectors to DIN		10 - 70 rm/se, 16 - 95 re/se		317
<b>Aluminium/copper compression cable lugs and connectors</b>				
Aluminum side of aluminum/copper compression cable lugs and connectors: crimping dies HA4, copper side of aluminum/copper compression cable lugs and connectors: crimping dies HD4		10 - 70 rm/se, 16 - 95 re/se		317
<b>Clamps</b>				
Clamps, C-type		4 - 35		317
<b>Cable end-sleeves</b>				
Cable end-sleeves		10 - 50		317
Twin cable end-sleeves		2 x 4 - 2 x 16		318
Twin cable end-sleeves for fine stranded conductors		2 x 4 - 2 x 16		318