

HK 60 VP/FT Hand-operated hydraulic crimping head 16 - 300 mm²



- ▶ Suitable for crimping tubular cable lugs and connectors "standard type" and fine and superfine stranded conductors to 300 mm²
- ▶ The patented centring system guarantees optimum crimps every time
- ▶ Closed crimping head - ideal for utility lines construction

Characteristics

- Quad-point indent crimping feature with patented centring system, no dies required
- Closed head with bolt interlock, rotatable, flip top style
- Light weight due to high quality aluminium housing
- 2-stage hydraulic system with fast feed and power stroke
- Simple and safe: Automatic retraction when operation is complete

| Technical data | |
|--|--------------------------|
| Crimping force | 55 kN |
| Crimping range | 16 - 300 mm ² |
| Length | 535 mm |
| Weight | 4.1 kg |
| Ambient temperature | -20 °C up to +40 °C |
| Item | Part-No. |
| Hand-operated hydraulic crimping tool 16 - 300 mm ² | HK60VPFT |
| Scope of supply | Part-No. |
| Steel carrying case | MK60VP |
| Gauge and 10 test cylinder | TS10B |
| Accessories | Part.-No. |
| Gauge and 10 test cylinder | TS10B |



| Suitable for | Connection material | Crimping range mm ² | Crimp profile |
|---|---------------------|--------------------------------|---------------|
| Copper tubular cable lugs and connectors | | | |
| Tubular cable lugs and connectors, standard type, tubular cable lugs for switchgear connections | | 16 - 300 | |
| Tubular cable lugs and compression joints for fine stranded conductors | | 16 - 300 | |