

MODEL No.

SH-5PDG

Punching capacity : 115.5mm diameter hole on 3.2mm thickness mild steel

SPECIFICATIONS

Reservoir capacity : 40 cc
Output force : 73 kN at 68.5 Mpa pressure

Punching capacity
Stainless Steel :
1.6 mm plate thickness
Mild steel :
3.2 mm plate thickness
Hole diameter :
up to 115.5 mm (4 inches)

SIZE

353 (L) mm

WEIGHT

2.4 kg

ACCESSORIES

Steel carrying case.

REMARKS

- * Self-contained hand hydraulic punch
- * Punching head rotates through 360 degrees for easy access in tight quarters
- * Slim design
- * Details information of punch is shown on page of SH-10

APPLICABLE PUNCH

- * A19-A75
- * B16-B104



SH-5PDG



SH-5PDG shown with standard accessories

FEATURES

The SH-5PDG is a portable hand hydraulic punch with swivel head for easy access to tight quarters.

It gives clean perforation through 3.2mm thick mild steel with a 4 inch hole.

SH-5PDG CONTENTS

- 1 SH-5PDG Hand hydraulic punch
- 2 Set bolts (3/8", 3/4")
- 3 Collars (Large, Medium, Small, Ex-small)
- 4 Steel carrying case

SH-5PDG PUNCH SET

- 1 SH-5PDG (A) SET : with A19-51 punch
- 2 SH-5PDG (B) SET : with B16-51 punch