

K 106/1 Hand-operated cutting tool for Al and Cu cables, class 2 to Ø 34 mm



Effortless operations thanks to energy-saving 2-stage ratchet system
Lightweight design with great cutting performance

Characteristics

- One-hand operation
- Not suitable for cutting steel or steel wire
- Handle with slip guard and inscription panel

Technical data		
Cutting range	max. 34 mm dia., e.g. 4 x 35 mm² NYY	
Length	260 mm	
Weight	0.6 kg	
Item		Part No.
Hand-operated cutting tool for Cu and Al cables to 34 mm dia.		K1061

K 106/2 Hand-operated cutting tool for AI and Cu cables, class 2 to Ø 62 mm



- > Effortless operations thanks to energy-saving 2-stage ratchet system
- Lightweight design with great cutting performance
- Cutting range to 62 mm

Characteristics

- One-hand operation
- Not suitable for cutting steel or steel wire
- Handle with slip guard and inscription panel

Technical data			
Cutting range	e.g. 4 x 120 mm² NYY, max. 62 mr	e.g. 4 x 120 mm² NYY, max. 62 mm dia.	
Length	260 mm	260 mm	
Weight	0.6 kg	0.6 kg	
Item		Part No.	
Hand-operated cutting tool for Cu and Al cables to 62 mm dia.		K1062	

K 103/1 Hand-operated cutting tool for Al and Cu cables to 60 mm dia.



- Energy-efficient 2-stage ratchet system
- For earth, plastic and rubber cables

Characteristics

- Not suitable for cutting steel or steel wire

Technical data			
Cutting range	e.g. 4 x 240 mm² NAYY, max. 60 n	e.g. 4 x 240 mm ² NAYY, max. 60 mm dia.	
Length	720 mm	720 mm	
Weight	4.5 kg	4.5 kg	
Item		Part No.	
Hand-operated cutting tool for Cu and Al cables to 60 mm dia.		K1031	

NEV