

EBS 8 ML / EBS 12 ML Battery powered hydraulic bolt cutter 8 mm dia. / 12 mm dia.



<u>IEC</u>

- For cutting cable channels, bolts and steel wire, medium-hard (e.g. ST 37)
 Slim cutting head ideal when space is critical
- > Powerful 10.8 V Li-Ion battery with charge status display

Characteristics

- Open head, rotatable
- Simple and safe: One-button operating concept for controlling all tool functions
- Comfortable and secure one-hand operation thanks to 2-component plastic housing with soft grips
- Effortless working thanks to low weight
- Simple and safe: Automatic retraction when operation is complete
- Maintenance display via LED

| Technical data | | | |
|--|---|----------|------|
| Cutting range | EBS8ML: max. 8 mm dia., EBS12ML: max. 12 mm dia. | | |
| Cutting force | EBS8ML: 15 kN, EBS12ML: 45 kN | | |
| Cutting time | EBS8ML: 2 s, EBS12ML: 4 s (depending on material thickness) | | |
| Number of cuts | ES8ML: 80 at silver steel 6 mm, EBS12ML: 105 at mild steel 10 mm | 1 | |
| Battery voltage | 10.8 V | | |
| Battery capacity | 1.5 Ah, Li-Ion | | |
| Charging time | approx. 40 min. | | |
| Weight incl. battery | EBS8ML: 1.2 kg, EBS12ML: 1.8 kg | | |
| Ambient temperature | -10 °C up to +40 °C | | |
| ltem | | Part No. | |
| Battery powered hydraulic bolt cutting tool 8 mm dia. | | EBS8ML | |
| Battery powered hydraulic bolt cutting tool 12 mm dia. | | EBS12ML | |
| Scope of supply | | Part No. | Page |
| Battery 10.8 V / 1.5 Ah, Li-Ion (16.2 Wh) | | RAML1 | 485 |
| Charger for 10.8 V Li-Ion batteries, 230 V | | LGML1 | 487 |
| Plastic case | | KKML | |