

TEMPORARY INSULATION

Safety equipment for insulation and temporary protection

Insulating platforms



TT015M

Use: used to provide insulation for a technician during 1st category work or using hand controlled 2nd and 3rd category separating tools (cutters, switches, etc.). Stands with screw-on legs are recommended for carrying since they occupy little space. Stands for outside use or for use in damp premises are fitted with skirts for water rejection. All the feet are inclined in order to keep the platform away from contact with vertical casings; the thread for screw-on feet is reinforced with a composite ring to prevent initial cracking due to the threading.

Insulating plastic interior platform **made in one piece**

Part N°	Current	Fixed feet	Patins	dim (cm)	Height under stand (mm)	Poids kg
TT015M 24KV	24 kV	x	4	50 x 50	150	3,60
TT015M 45KV	45 kV	x	4	50 x 50	237	3,90



TT016

Insulating plastic interior platform

Part N°	Current	Fixed feet	Screw-on feet	dim (cm)	Height under stand (mm)	Weight kg
TT016 24KV	24 kV		x	50 x 50	150	3,60
TT016 45KV	45 kV		x	50 x 50	237	3,90
TT016 63KV	63 kV		x	50 x 50	317	4,10



**TT025
TT02
TT03**

Insulating wooden interior platform

Part N°	Current	Fixed feet	Screw-on feet	dim (cm)	Height under stand (mm)	Weight kg
TT02	24 kV		x	50 x 50	147	4,95
TT025 45KV	45 kV		x	50 x 50	235	5,30
TT03 63KV	63 kV		x	50 x 50	315	6,00



TT018

Insulating plastic exterior platform. Dimensions: 50 x 50 cm

Part N°	Current	Fixed feet	Screw-on feet	Skirts	Height under stand (mm)	Weight kg
TT018 24KV	24 kV		x	2	245	4,15
TT018 45KV	45 kV		x	3	362	4,60
TT018 63KV	63 kV		x	3	413	4,80



TT017

Insulating wooden exterior platform. Dimensions: 50 x 50 cm

Part N°	Current	Fixed feet	Screw-on feet	Skirts	Height under stand (mm)	Weight kg
TT017 24KV	24 kV		x	2	242	5,42
TT017 45KV	45 kV		x	3	360	6,35
TT017 63KV	63 kV		x	3	410	6,40



TT01

TT01 Special wooden platform **"electro emergency set"** (TC106 and TC106S) (see chapter 2)

Part N°	Current	Fixed feet	Screw-on feet	dim (cm)	Height under stand (mm)	Weight kg
TT01	25 kV	x		33 x 46	147	3,15

Open top (standard 2 bars): in hardwood, coated with waterproof varnish (2 coats). Mortice and tenon joint. The corners holding the feet are reinforced with plywood. Insulated feet in PVC, with anti-slip pads. Dimensions 330 x 460 x 180 mm - Weight 3,150 kg.

Use: special insulated stand for electro emergency box TC 106GB.