

No.2 KOHLER ROAD, SANSHUI CENTRAL INDUSTRIAL PARK, LEPING TOWN, SANSHUI DIST., FOSHAN, GUANGDONG, PRC POST CODE 528137 广东省佛山市三水区乐平镇三水中心工业园区科勒大道2号 邮编: 528137



					切割图/安装访
换。	REMOVE EXISTING LAVATORY • Turn off the water supply to the faucet.	Faucet 龙头 Supply Lines 供水管	拆除旧脸盆 • 关掉水龙头的供水源。 	CAUTION: Risk of personal injury or product damage. Large lavatories are very heavy. Get help lifting the lavatory into place.	▲ 小心:提防身体受 产品。因大型脸盆 需找人帮您一起搬 放。
-小心检验新 l.装盒内 ,到	 Open the faucet valves, then disconnect the supply lines. 	Shut-off Valve 止水阀 Drain Assembly 排水裝置	,● 打开龙头阀门,然后除开供水管。		
孔口与新脸	Disconnect the drain assembly and remove the trap.Remove the existing lavatory.		再旋开排水装置,并拿开弯管。移走旧脸盆。	 Immediately wipe away any excess sealant, and fill any voids as needed. Verify that the lavatory has not 	 立即擦去多余的封边朋外缘与台面间有缝隙, 密。 检查脸盆的位置准确。
, 标划正确	INSTALL NEW		安装新脸盆	moved out of position.Allow the sealant to cure for at	• 最少待三十分钟,让
与美式洗脸 之不相配。	LAVATORY			least 30 minutes before proceeding.	后,方可继续进行安装
ASME标准	 Cut the template on the cutout line. Position the template on the countertop to ensure clearance between the lavatory, faucet, and backsplash. 	TEMPLATE 安装模板	 将切割图沿切割线切出。 将切割图放在盥洗台上,确保脸盆、水 龙头和防溅挡板之间有足够的距离。 	 Connect the faucet supply lines. Connect the drain assembly. Open the faucet valves, and check for leakage. 	 联接水龙头供水管。 联接排水装置。 开启水龙头阀门,检漏。
	 Verify cabinet clearance beneath the countertop. 		 查核盥洗台下的储物柜也有足够空间。 	Clean up with a non-abrasive cleaner.	• 用非腐蚀性清洁剂来清
	Trace the template on the countertop with a pencil.		• 用炭笔沿切割图在盥洗台面划线。	IMPORTANT CONSUMER	用户须知 (护理和清洁)
	 Re-check the clearance between the lavatory, faucet, backsplash, and cabinet. Adjust the template accordingly. 		 再次检查脸盆、水龙头、防溅水板及储 物柜的空间及距离。如有需要可调校切 割图的位置。 	INFORMATION (CARE AND CLEANING)	
	 Drill a 13mm hole on the inside of the cutout opening. Cut the opening in the countertop along the inside edge of the pencil line. 		 用一个13mm的钻头,在切割口内侧钻一 个导孔。 沿着自切割图勾划出来的铅笔线内侧切 开台面。 	To keep your lavatory looking new, make sure you rinse it out thoroughly after each use. DO NOT USE ABRASIVES on this product, as they will scratch and ruin the surface. Stubborn stains, paint, or tar can be	为保持脸盆光洁如新,须确保每次 底冲洗干净, 切勿使用腐蚀性 的清 免刮花及破坏脸盆的表面。要清 垢,油漆或柏油,可使用松油或 剂。
	 Temporaily position the lavatory in the opening, and adjust to fit. 		• 暂将脸盆放入台面开口,校正位置。	removed with turpentine or paint thinner. Do not use the product in the water below	不要在 0℃ 以下的水环境中使用。
Unit: mm 单位: 毫米	CAUTION: Risk of personal injury or product damage. Large lavatories are very heavy. Get help lifting the lavatory into place.		▲ 小心:提防身体受伤或损坏产品。因 大型脸盆相当重,需找人帮您一起搬 动及安放。	0°C. CAUTION: Please do not use hard materials (like scouring pad) to clean product surface, especially the product logo.	▲ 警告:请勿使用钢丝球等码 洗产品表面,特别是产品商:
	 Trace a pencil line around the outside edge of the lavatory. 		• 用炭笔沿脸盆外缘在盥洗台上划线。		
epth 査深	 Remove the lavatory. Install the faucet and drain according to the manufacturers instructions. 		 然后将脸盆移开。 按照制造商的指引,安装水龙头和排水管道。 		
	 Apply two beads of sealant to the inside of the pencil line. 	C.C.	• 沿炭笔导线内侧涂两滴封边胶。		
22	• Spread the sealant evenly with a putty knife.		• 用涂油灰刀将其抹匀。		
	• Carefully position the lavatory in the cutout, and press down firmly.		 小心地将脸盆置于台面切口适当位置, 向下按牢。 		

8# MENGSHAN RD, ECONOMIC DEVELOPMENT ZONE OF HUANTAI, ZIBO, SHANDONG, CHINA POST CODE: 256410 山东省淄博市桓台经济开发区蒙山路8号 邮编: 256410

502.8mm

© Copyright Kohler China Investment Co., Ltd. 2016 ©版权为科勒(中国)投资有限公司所有 2016

FINISHED WALL/BACK SPLASH 完工墙面 / 后防溅挡板

