

SPECIFICATION

CONNECTION	
Video In	HDMI type-A ×4
Video Out	HDMI type-A PGM ×1 HDMI type-A Multiview ×1 USB2.0 type C ×1 (Streaming on PC) Assignable HDMI 1~4, PGM, Clean PGM, PVW, Color bar, Multiview
Audio In	MIC/ Line level (3.5mm stereo audio) ×2
PC Control Port	LAN×1
Media Library	USB type-A ×1(USB disk port for image import and firmware upgrade)
Tally Port	DB-15 ×1
Power In	DC 12V ×1
FUNCTIONS	
Transitions	T-Bar/AUTO/ CUT
Effects	Wipe (9×2 patterns)/ Mix/ DIP/ Pattern/ Still(freeze)/ MUTE/ FTB
Layouts	2 styles of Multiview layout (6 windows and status)
Keys	Upstream Key: Luma Key ×1/ Chroma Key ×1/ PiP ×2/ POP Downstream Key: DSK ×1/ Logo ×1
Audio Mixer	HDMI ×4 and MIC/ Line level ×2; Audio delay: 0-500ms
Media	Default image: 49 preset patterns Local image: up to 16 imported images Capture image: up to 16 captured images
Generators	Pattern generator ×1 Color generators ×2
STANDARDS	
HDMI In Format Support	1080p 60/ 59.94/ 50/ 30/ 29.97/ 25/ 24/ 23.98 1080i 50/ 59.94/ 60 720p 60/ 59.94 /50/ 30/ 29.97/ 25/ 24/ 23.98 576i 50, 576p 50, 480p 59.94/ 60, 480i 59.94/ 60
HDMI PGM Out	1080p 60/ 59.94/ 50/ 48/ 47.95/ 30/ 29.97/ 25/ 24/ 23.98; 1080i 60/ 59.94/ 50
HDMI Multiview Out	1080p 60/ 59.94/ 50/ 48/ 47.95/ 30/ 29.97/ 25/ 24/ 23.98; 1080i 60/ 59.94/ 50
HDMI Color Space	RGB/ YUV
USB Capture Out	MJPEG, Up to 1080p 60
Media Format	USB disk format support: FAT32, Ext3, Ext4, up to 256GB

	Image format support: png, bmp, jpg, gif, jpeg, ppm, pbm, tif, jps, mpo, tga Logo format support: png, bmp, jpg, gif, jpeg, ppm, pbm, tif, jps, mpo, tga Logo size support: 10×10 pixel to 600×600 pixel
OTHERS	
Power	Wide voltage: 7~24V; Operating power:12W (12V 1A)
Dimension (LWD)	244.5 × 143.2 × 44.5mm
Weight	Net: 1030g; Gross: 1500g
Temperature	Working: -20°C~60°C, Storage: -30°C~70°C
Accessories	Power supply (12V 2A) ×1; USB cable (type A-C) ×1; Tally connector (DB-15) ×1