

HS-2200 Specifications

| HS-2200 6 input HD broadcast quality Mobile Studio | |
|--|--|
| Video Standard | HD & SD |
| Video Format | 1080i 50/59.94/60Hz 720p 50/59.94/60Hz 576i 50Hz 480i 59.94Hz |
| Input Routable / Crosspoint | All 6, repeatable |
| Video Input | 6x HD-SDI, 2x HDMI (on CH5 & 6) |
| Computer Graphic Interface | 2 via HDMI |
| Down-converted Output | N/A |
| Video Output | 5x SDI Outputs assignable: AUX 1-4, PGM, PVW, PGM Clean or multiview 1x HDMI multi-view |
| Audio Input | 4x Balanced XLR |
| Audio Output | 2x Balanced XLR |
| Embedded Audio Support | Input up to 16 channels, Output 4 channels |
| Audio Delay Calibration | N/A |
| A+V Switching | Yes |
| USK | N/A |
| DSK | 1, support Lumakey & Linear key (Key / Fill) |
| Picture in Picture | 2 |
| Logo Insertion | 2 (or 1 logo + 1 clock) |
| Title Creator | Yes, CG-200 software free download |
| Built-in Audio Mixer | N/A |

| | |
|---------------------------|--|
| Built-in Monitor Display | 17.3" HD TFT LED backlit, 1600x900 pix |
| Built-in Intercom & Tally | 8 channels (4 belt-packs incl.) |
| Special Features | Built in TC-200 CG interface 6x6 matrix seamless switch |
| Dimension (LxWxH) | 455 x 355 x 134 mm |
| Weight | 16.5 Lbs (7.5 kg), Reinforce Plastic Case |
| Power | DC 12V, 5A |
| Operating Temp. Range | 0~40 °C |
| Options | CB-22H/23H/46/47/60/61/62 |
| What's in the Box | <ul style="list-style-type: none"> 1 x HS-2200 Unit 1 x AD Switch DC 12V with AC Cord 1 x CB-41 / XLR to XLR Cable 4 x CB-3 / XLR cable 1 x USB Light 1 x Goose neck MIC 4 x Headphone Microphone 4 x ITC-100SL 4 x Tally light 4 x Velcro 1 x Thank You Card |