

MS-2850 Specifications

MS-2850 HD/SD 8/12-Channel Mobile Video Studio	
Digital Video Switcher	SE-2850
Rack Mount LCD	TLM-170LM x1 (MS-2850A/C/E/F) TLM-170VM x1 (MS-2850G/H)
Recorder	HDR-70 x1
Intercom/Tally System	ITC-100 w/4 Belt packs
Vectorscope	Built in TLM-170VM (MS-2850G/H)
Audio Mixer	AD-100M (MS-2850A/E/G) AD-200 (MS-2850C/F/H)
Power Distributor	PD-2A (All MS-2850 configurations) PD-6 (MS-2850G/H)
Return Video (8-CH CV)	RP-64 (MS-2850G/H)
Camera Power Distributor	PD-6A (MS-2850G/H)
4K Multicamera Processor	KMU-100 (MS-2850E/F)
HD/SD SDI Amplifier	VP-445 (MS-2850G)
Rack System Integration	8RU Flight Case
Weight	65 kg
Operating Temp. Range	0~40 °C
Options	
CB-22H/23H Repeater	VP-781
SDI/ITC Cable	CB-46/47 (30/50m)
ITC/Tally Cable	CB-3/4 (20m/50m)
HDMI Cable	CB-60/61/62 (30m/50m/100m)

100m SDI Repeater

VP-633 / VP-634