

OBV-2850 Specifications

OBV-2850 HD/SD 8/12-Channel Mobile Video Studio	
Digital Video Switcher	SE-2850
Rack Mount LCD	TLM-170VR x2
Recorder	HDR-70 x1
Intercom/Tally System	ITC-100 w/4 Belt Packs
Vector Scope	Built-in TLM-170VR
Audio Mixer	AD-200
Power Distributor	PD-2A
Camera Control System	CCU-100 x1 (OBV-2850C)
Camera Power Distributor	PD-6A (OBV-2850C)
Video Streaming Server	NVS-33
4K Multicamera Processor	KMU-100 (OBV-2850B)
HD/SD SDI Amplifier	VP-445 x1, VP-633 x3
Rack System Integration	27RU Mobile Rack System x 2 ?Asia: 25RU Mobile Rack System (x 2)
Weight	85 kg
Operating Temp. Range	0~40 °C
Options	
Camera Power Regulator	DDC-4012H (9-30V to DC12V)
Redundant Power (360W)	PD-4A
CB-22H/23H Repeater	VP-781
SDI/ITC Cable	CB-46/47 (30/50m)

ITC/Tally Cable	CB-3/4 (20m/50m)
HDMI Cable	CB-60/61/62 (30m/50m/100m)
100m SDI Repeater	VP-634
What's in the Box Part1	<ul style="list-style-type: none"> 1 x OBV-2850 product 4 x ITC-100SL with Carry Bag 4 x Tally LED TD-3 4 x Headphone 1 x Goose neck MIC 1 x Goose neck LED light 4 x XLR Cable + CON 20M 4 x GPI Cable Stereo 1.2M 2 x AC Power Cord 1 x Y type USB cable 5 x 120mm cable tie 10 x 200mm cable tie 1 x Y type 2 pin MOLEX cable 2 x 2.5" HDD enclosure 10 x Screw M3*4mm 10 x Anti-vibration screw + M5*10 washer
What's in the Box Part2	<ul style="list-style-type: none"> 2 x ISO screw 2*6mm 2 x HD sticker 4 x Blank sticker 4 x Black Velcro 36cm 1 x Thank You Card