

TVS-3000 Specifications

TVS-3000 4K 3D Tracking AR Virtual Studio System	
Tracking/Trackless	3D Tracking & Trackless
Video Input	4K mode: 6G-SDI x 2 or 12G-SDI x 1 HD mode: 3G-SDI x 3
Video Output	4K mode: HDMI 2.0 x 1 HD mode: 3G-SDI x 4 + HDMI x 1
Video Input/Output Format	SDI Input/Output: 2160p 60/50/30/25 (Input only) 1080p 30/25 1080i 60/50 720p 60/50/30/25 HDMI Output: 2160p 60/50/30/25 1080p 60/50/30/25 720p 60/50/30/25
Audio Input	Mini Phone Jack x 1 SDI audio embedded
Operation Monitor	DP x2
Tally	Coming Soon
Downstream Key	3
Media	3(DDR)
Virtual Studio	10 & Unlimited download from datavideovirtualset.com
Still Picture	1
Still Text	2
Keyer	Chromakey upto 8CH

Recording	Lossless 4:2:2 (.avi) H.265 (.mov) H.264 (.mp4;.wmv) MPEG-2 (.ts;.mxf)
Live Streaming Protocols	TS over UDP TS over TCP RTMP RTMPS RTSP
Hard Disk Capacity	4TB HDD + 500G SSD
Dimension (LxWxH)	480 x 470 x 178mm
Weight	13.6 kg
Operating Temp. Range	0~40 °C
Power	AC 100-240V 750W
What's in the Box	1 x TVS-3000A Main Unit 1 x Power AC Cord 1 x USB Mouse 1 x RMC-285 Unit(Include D-Sub 9 PIN Cable + DC 12V power adaptor) 1 x 802.11AC Antenna / or USB dongle 1 x LBK-2 1 x Thank You Card