

DA 2698

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.



- Customised kitchen design - fully integrated in 880mm width
- Unique user convenience – Con@ctivity
- Powerful - 640m³/h on the booster setting
- Energy-efficient and quiet - powerful ECO motor
- Elegant and efficient - edge extraction panels

EAN: 4002516001492 / material number: 10851400

Construction type	
Integrated extractor	•
Design	
Colour	Stainless steel
Edge extraction	•
Operating modes	
Type of air guide	Convertible
Recirculation conversion kit (order separately)	DUU 151
User convenience	
Networking with Miele@home	•
Automatic function Con@ctivity 3.0 (WiFi)	•
Electronic controls	•
Light-touch controls	•
Miele@mobile app	•
Power levels (excluding booster levels)	3
Programmable Booster level switch-off	•
Run-on time 5 / 15 min.	•
Grease filter saturation indicator programmable	•
Active charcoal filter saturation indicator programmable	•
Cleaning convenience	
Easy-to-clean canopy interior – CleanCover	•
Efficiency and sustainability	
ECO package	•
Filter system	
Number of dishwasher safe stainless steel grease filters	2
Lighting	
LED	•
Light intensity in Lx	650
Colour temperature in K	3,500
Dimmer function	•
Fan	
Dual-action fan	•
ECO motor (DC motor)	•
Air throughput with max. duct diameter in extraction mode (not for external version)	
Air throughput in Level 1 (m ³ /h)	200
Air throughput in Level 2 (m ³ /h)	300
Air throughput in Level 3 (m ³ /h)	400
Air throughput in booster level 1 (m ³ /h)	640
Sound power in Level 1 (dB(A) re 1 pW)	36
Sound power in Level 2 (dB(A) re 1 pW)	44
Sound power in Level 3 (dB(A) re 1 pW)	51
Sound power in booster level 1 (dB(A) re 1pW)	62
Sound pressure in Level 1 (dB(A) re 20 µPa)	22
Sound pressure in Level 2 (dB(A) re 20 µPa)	30
Sound pressure in Level 3 (dB(A) re 20 µPa)	37
Sound pressure in booster level 1 (dB(A) re 20µPa)	48
Sound pressure in booster level 2 (dB(A) re 20µPa)	48

more information:
<http://www.miele.co.uk/domestic>

For further information please see next page...

DA 2698

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.



Air throughput in recirculation mode	
Air throughput in Level 1 (m ³ /h)	135
Air throughput in Level 2 (m ³ /h)	220
Air throughput in Level 3 (m ³ /h)	365
Air throughput in booster level 1 (m ³ /h)	535
Sound power in Level 1 (dB(A) re 1 pW)	47
Sound power in Level 2 (dB(A) re 1 pW)	55
Sound power in Level 3 (dB(A) re 1 pW)	62
Sound power in booster level 1 (dB(A) re1pW)	74
	74
Sound power in booster level 2 (dB(A) re1pW)	74
	74
Sound pressure in Level 1 (dB(A) re 20 µPa)	32
Sound pressure in Level 2 (dB(A) re 20 µPa)	41
Sound pressure in Level 3 (dB(A) re 20 µPa)	48
Sound power in booster level 1 (dB(A) re1pW)	59
	59
Sound pressure in booster level 2 (dB(A) re20µPa)	59
	59
Safety	
Safety switch-off	•
Technical data	
Canopy width in mm	880
Canopy height in mm	64
Canopy depth in mm	293
Minimum height above electric hobs in mm	450
Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm	650
Net weight in kg	14.0
Length of supply lead in m	1.5
Standard plug fitted	•
Total rated load in kW	0.09
Voltage in V	230
Fuse rating in A	10
Number of phases	1
Installation notes	
Extraction ducting connection at top	•
Extraction connection at top and rear	•
Diameter of extraction ducting connection in mm	150
Combination with WiFi-enabled Miele hob	recommended