

EAN: 4002516156819 / material number: 11093500

#### H 7264 BP

### Oven

seamless design with clear text, networking & pyrolytic cleaning.



- Clear text display with sensor controls – DirectSensor S
- Minimal cleaning effort Pyrolytic cleaning
- Especially light dough and nicely browned crusts – Moisture plus
- Network-enabled WiFi appliance Miele@home
- Achieve perfect results with ease automatic programmes



Model and design	
Built-in oven	•
PureLine	•
Appliance colour	Stainless steel/Clean Steel
Convenience features	
Rapid heat-up	•
Operating modes	
Defrosting	•
Auto roast	•
Grill	•
Fan plus	•
Intensive bake	•
Moisture plus	•
Moisture plus with Fan plus	•
Conventional heat	•
Bottom heat	•
Fan grill	•
User convenience	
Networking with Miele@home	•
Display	DirectSensor S
SoftClose	•
MultiLingua	•
Time of day display	•
Minute minder	•
Programmable start of cooking duration	•
Programmable end of cooking duration	•
Actual temperature display	•
Target temperature display	•
Audible signal when target temperature is reached	•
Recommended temperature	•
Individual settings	•
Efficiency and sustainability	
Energy efficiency class (A+++ - D)	A+
Power rating in off mode in W	0.5
Power rating in standby mode in W	1.0
Power rating in networked standby in W	2.0
Time until automatic switch to standby in min	20
Time until automatic switch to networked standby in min	20
Time until automatic switch to off mode in min	20
Cleaning convenience	
Stainless steel front with CleanSteel finish	•
Pyrolytic self-cleaning	•
Catalyser	Unheated
Hinged grill heater element	•
CleanGlass door	•
Safety	
Appliance cooling system and touch-cool fronts	•

more information: http://www.miele.co.uk/domestic

Safety switch-off
System lock

Door lock during pyrolytic cleaning



### H 7264 BP

### Oven

seamless design with clear text, networking & pyrolytic cleaning.



Technical data	
Oven compartment volume in I	76
No. of shelf levels	5
Numbered shelf levels	•
Oven light	1 halogen spot
Appliance width in mm	595
Appliance height in mm	596
Appliance depth in mm	569
Weight in kg	47.0
Total rated load in kW	3.6
Voltage in V	220-240
Number of phases	1
Fuse rating in A	16
Length of supply lead in m	2
Standard accessories	
Baking tray with PerfectClean	1
Universal tray with PerfectClean	1
Baking and roasting rack with PerfectClean	1


## Míele

### H 7264 BP

### Oven

seamless design with clear text, networking & pyrolytic cleaning.






H226x-1B/BP/E/EP/I/IP, H2760B/BP, H28x0B/BP, H7x6xB/BP/BPX installation drawings

- Netzanschlussleitung, L=1500 mm
   In diesem Bereich kein Anschluss
   Lüftungsausschnitt min. 150 cm²


H2760B/BP, H28x0B/BP, H7x6xB/BP/BPX, installation drawings

22 mm - glass 23.3 mm - metal



H2760B/BP, H28x0B/BP, H7x6xB/BP/BPX, installation drawings

22 mm - glass 23,3 mm - metal



H226x-1B/BP/E/EP/I/IP, H2760B/BP, H28x0B/BP, H7x6xB/BP/BPX, installation drawings


### Míele

#### H 7264 BP

### Oven


seamless design with clear text, networking & pyrolytic cleaning.






H226x-1B/BP/E/EP/I/IP, H2x6xB/BP, H7x6xB/BP/BPX, installation drawings

If the oven is to be installed under a hob, follow the instructions for installing the hob and the height of the hob.




DG2840, DG7x40, DGC7x4x, DG7x6x, DGC7x6x, DGD7635, DGM7x4x, DO7, H28B/BP, H7x4xB/BM/BP, H7x6xB/BP, installation drawing

- 1) 400 mm 2) 360 mm 3) 47 mm 4) 24 mm 5) 32.5 mm



- DG7x40, DGC7x4x, DGC7x6x, DG7635, DGM7x4x, DO7, H2860B/BP, H7240BM, H7x40BM, H7x4xB/BP, H7x6xB/BP, installation drawings

- 1) 400 mm 2) 360 mm 3) 47 mm 4) 27 mm 5) 32.5 mm



H226x-1B/BP/E/EP/I/IP, H2760B/BP, H28x0B/BP, H7x40BM/BMX, H7x6xB/BP/BPX, installation drawings


# Míele

### H 7264 BP

### Oven


seamless design with clear text, networking & pyrolytic cleaning.





 $\ensuremath{\mathsf{H2xxx}\text{-}1}$  B/BP/E/I/IP, H7xxx B/BP/BM/BMX, installation drawings

22 mm - glass 23,3 mm - metal



H2xxx-1 B/BP/E/I/IP, H7xxx B/BP/BM/BMX, installation drawings

22 mm - glass 23,3 mm - metal