


12FW76

LF Drivers - 12.0 Inches





- 1000 W continuous program power capacity
- 76 mm (3 in) copper voice coil
- 55 - 3000 Hz response
- 100 dB sensitivity
- Aluminium demodulating ring allows a very low distortion figure



12FW76

LF Drivers- 12.0 Inches



SPECIFICATIONS

Nominal diameter	320 mm (12.0 in)
Nominal impedance	8 Ω
Minimum impedance	6.8 Ω
Nominal power handling ¹	500 W
Continuous power handling ²	1000 W
Sensitivity (1W/1m) ³	100.0 dB
Frequency range	55 - 3000 Hz
Voice coil diameter	76 mm (3.0 in)
Winding material	Copper
Former material	Glass Fibre
Winding depth	19 mm (0.75 in)
Magnetic gap depth	11 mm (0.43 in)
Flux density	1.35 T

DESIGN

Surround shape	Triple Roll
Cone shape	Exponential
Magnet material	Ferrite
Spider	Single
Pole design	T-Pole
Woofer cone treatment	WP Waterproof Front Side
Recommended enclosure	40.0 dm ³ (1.41 ft ³)
Recommended tuning	65 Hz

PARAMETERS

F _s	54 Hz
R _e	5.1 Ω
Q _{es}	0.18
Q _{ms}	3.8
Q _{ts}	0.18
V _{as}	45.0 dm ³ (1.6 ft ³)
S _d	522.0 cm ² (80.9 in ²)
η _o	3.7 %
X _{max}	7.0 mm
X _{var}	10.0 mm
M _{ms}	75 g
Bl	26.4 Txm
Le	1.4 mH
EBP	300 Hz

MOUNTING AND SHIPPING INFO

Overall diameter	315 mm (12.4 in)
Bolt circle diameter	298 mm (11.7 in)
Baffle cutout diameter	283.0 mm (11.1 in)
Depth	147 mm (5.79 in)
Flange and gasket thickness	12 mm (0.47 in)
Air volume occupied by driver	3.0 dm ³ (0.1 ft ³)
Net weight	8.5 kg (18.7 lb)
Shipping units	1
Shipping weight	9.2 kg (20.3 lb)
Shipping box	340x340x170 mm (13.4x13.4x6.7 in)

SERVICE KIT

RCK12FW768

1. 2 hours test made with continuous pink noise signal (6 dB crest factor) within the range F_s-10F_s. Power calculated on rated minimum impedance. Loudspeaker in free air.
2. Power on Continuous Program is defined as 3 dB greater than the Nominal rating.
3. Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.